

# Diode block - EMG 22-DIO 7M - 2950077

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Diode module, with 7 diodes, common anode, diode type 1N 4007

The illustration shows a combination of versions EMG 22-DIO 7 P, EMG 45-DIO14 P and EMG 90-DIO 32 P

## Product Features

- Spark-suppression diodes for limiting surge voltages of inductive loads
- Electrical decoupling of messages in fault reporting systems



## Key commercial data

<b>package_quantity</b>	10
<b>GTIN</b>	4017918083946

## Technical data

### Dimensions

<b>Width</b>	22.5 mm
<b>Height</b>	75 mm
<b>Depth</b>	55 mm

### Ambient conditions

<b>Ambient temperature (operation)</b>	-20 °C ... 50 °C
<b>Ambient temperature (storage/transport)</b>	-40 °C ... 70 °C

### General

<b>Diode type</b>	1 N 4007
<b>Max. operating voltage</b>	250 V AC
<b>Peak reverse voltage per diode</b>	1300 V
<b>Reverse current per diode</b>	5 µA
<b>Conducting state voltage per diode</b>	approx. 0.8 V
<b>Conducting state current per diode</b>	0.7 A (with single load)
<b>Conducting state current per diode</b>	0.5 A (with simultaneous loads)
<b>Surge voltage category</b>	III, basic insulation (as per EN 50178)

# Diode block - EMG 22-DIO 7M - 2950077

## Technical data

### General

<b>Mounting position</b>	any
<b>Assembly instructions</b>	In rows with zero spacing

### Connection data

<b>Conductor cross section solid min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section solid max.</b>	4 mm <sup>2</sup>
<b>Conductor cross section stranded min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section stranded max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section AWG/kcmil min.</b>	24
<b>Conductor cross section AWG/kcmil max</b>	12
<b>Stripping length</b>	8 mm
<b>Screw thread</b>	M3
<b>Connection method</b>	Screw connection

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27250312
<b>eCl@ss 4.1</b>	27260801
<b>eCl@ss 5.0</b>	27260801
<b>eCl@ss 5.1</b>	27260801
<b>eCl@ss 6.0</b>	27242602
<b>eCl@ss 7.0</b>	27371010
<b>eCl@ss 8.0</b>	27371010

### ETIM

<b>ETIM 2.0</b>	EC001432
<b>ETIM 3.0</b>	EC001597
<b>ETIM 4.0</b>	EC001597
<b>ETIM 5.0</b>	EC000683

### UNSPSC

<b>UNSPSC 6.01</b>	30211506
<b>UNSPSC 7.0901</b>	39121008
<b>UNSPSC 11</b>	39121008
<b>UNSPSC 12.01</b>	39121008
<b>UNSPSC 13.2</b>	39121008

## approvals

GOST /

### Approval details

## Diode block - EMG 22-DIO 7M - 2950077

approvals



accessories

EMG-GKS 12 - 2947035



---

Drawings

# Diode block - EMG 22-DIO 7M - 2950077

Circuit diagram

