

Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse terminal block with LED for mounting on NS 35, for miniature circuit breakers, terminal width: 8.2 mm, color: Black

Product Features

- Versions with LED for indicating that a fuse has blown
- The ST 4-FSI/C fuse terminal block accommodates flat-type fuses according to ISO/DIS 8820/DIN 72581-3 or the TCP .../DC32V thermal miniature circuit breaker as the fuse element

Key commercial data

package_quantity	50
GTIN	4017918890469

Technical data

General

Number of levels	1
Number of connections	2
Mounting type	DIN rail: 35 mm
Color	black
Surge voltage category	III
Insulating material	PA
Inflammability class according to UL 94	V0

Electrical data

Fuse	C
Fuse type	Flat
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Power loss	on request
Maximum current with single arrangement	30 A
Voltage LED	24 V DC
Current LED	2 mA

Dimensions

Width	8.2 mm
Height NS 35/7,5	43.5 mm

Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

Technical data

Dimensions

Height NS 35/15	51 mm
-----------------	-------

Connection data

Conductor cross section solid min.	0.08 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section stranded min.	0.08 mm ²
Conductor cross section stranded max.	4 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	10
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.14 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	4 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.14 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	4 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1 mm ²
Connection method	Spring-cage connection
Internal cylindrical gage	A4

classifications

eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116
eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410

Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

classifications

UNSPSC

UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

CSA / UL Recognized / cUL Recognized / GOST / GL / RS / GOST / cULus Recognized /

Approval details

CSA		
Usegroups	B	C
Nominal voltage UN	300 V	300 V
Nominal current IN	10 A	10 A
mm ² /AWG/kcmil	28-10	28-10

UL Recognized		
Usegroups	B	C
Nominal voltage UN	300 V	300 V
Nominal current IN	30 A	30 A
mm ² /AWG/kcmil	28-10	28-10

cUL Recognized	
Nominal voltage UN	300 V
Nominal current IN	30 A
mm ² /AWG/kcmil	28-10


GOST

GL

RS

Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

approvals



accessories

Screwdriver tools

SZF 1-0,6X3,5 - 1204517



Documentation

ST-IL - 3039900



Bridge

FBS 2-8 - 3030284



FBS 3-8 - 3030297



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

FBS 4-8 - 3030307



FBS 5-8 - 3030310



FBS 10-8 - 3030323



FBS 6-8 - 3032470



FBSRH 2-8 - 3033802



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

FBSRH 3-8 - 3033803



FBSRH 4-8 - 3033804



FBSR 2-6 - 3033715



FBSR 3-6 - 3001594



FBSR 4-6 - 3001595



FBSR 5-6 - 3001596



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

FBSR 10-6 - 3033716



Terminal marking

ZB 8:UNBEDRUCKT - 1052002



UC-TM 8 - 0818072



UCT-TM 8 - 0828740



ZBF 8:UNBEDRUCKT - 0808781



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

UC-TMF 8 - 0818137



UCT-TMF 8 - 0828748



Labeled terminal marker

ZB 8 CUS - 0825011



UC-TM 8 CUS - 0824597



UCT-TM 8 CUS - 0829616



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

ZB 8,LGS:FORTL.ZAHLEN - 1052015



ZB 8,QR:FORTL.ZAHLEN - 1052028



ZB 8,LGS:L1-N,PE - 1052413



ZBF 8 CUS - 0825030



ZBF 8,LGS:FORTL.ZAHLEN - 0808804



UC-TMF 8 CUS - 0824654



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

UCT-TMF 8 CUS - 0829672



Test plug terminal block

MPS-MT - 0201744



PS-6 - 3030996



PS-6/2,3MM RD - 3038736



PAI-4-FIX BU - 3032729



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

PAI-4-FIX OG - 3034455



PAI-4-FIX YE - 3032745



PAI-4-FIX RD - 3032732



PAI-4-FIX GN - 3032758



PAI-4-FIX BK - 3032774



PAI-4-FIX GY - 3032790



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

PAI-4-FIX VT - 3032761



PAI-4-FIX BN - 3032787



Insulating sleeve

MPS-IH WH - 0201663



MPS-IH RD - 0201676



MPS-IH BU - 0201689



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

MPS-IH YE - 0201692



MPS-IH GN - 0201702



MPS-IH GY - 0201728



MPS-IH BK - 0201731



ISH 4/0,5 - 3002885



ISH 4/1,0 - 3002898



Fuse modular terminal block - ST 4-FSI/C-LED 24 - 3036505

accessories

End cover

DP PS-6 - 3036738



Drawings

Circuit diagram

