

Spring cage ground terminal block - ST 16-PE - 3036165

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Spring cage ground terminal block, Connection method: Spring-cage connection, Cross section: 0.2 mm² - 25 mm², AWG: 24 - 4, Width: 12.2 mm, Color: green-yellow, Mounting type: NS 35/7,5, NS 35/15



Key commercial data

package_quantity	25
GTIN	4017918821098

Technical data

General

Number of levels	1
Number of connections	2
Color	green-yellow
Insulating material	PA
Inflammability class according to UL 94	V0

General

Maximum load current	90 A (with 25 mm ² conductor cross section)
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-2
Nominal current I _N	76 A
Open side panel	ja
Shock protection test specification	DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection	guaranteed
Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Static insulating material application in cold	-60 °C

Dimensions

Width	12.2 mm
-------	---------

Spring cage ground terminal block - ST 16-PE - 3036165

Technical data

Dimensions

Length	80 mm
Height NS 35/7,5	51.5 mm
Height NS 35/15	59 mm

Connection data

Connection in acc. with standard	IEC 60947-7-2
Connection method	Spring-cage connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	25 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	4
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	16 mm ²
Min. AWG conductor cross section, stranded	24
Max. AWG conductor cross section, stranded	6
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	16 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	16 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	1.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	4 mm ²
Stripping length	18 mm
Internal cylindrical gage	A7

classifications

eCl@ss

eCl@ss 4.0	27141118
eCl@ss 4.1	27141118
eCl@ss 5.0	27141118
eCl@ss 5.1	27141118
eCl@ss 6.0	27141141
eCl@ss 7.0	27141141
eCl@ss 8.0	27141141

ETIM

ETIM 2.0	EC000901
ETIM 3.0	EC000901
ETIM 4.0	EC000901

Spring cage ground terminal block - ST 16-PE - 3036165

classifications

ETIM

ETIM 5.0	EC000901
-----------------	----------

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

IECEX / ATEX / CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / GOST / LR / GL / BV / DNV / RS / KR / NK / IECCEB Scheme / GOST / cULus Recognized /

Approval details

IECEX	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	1.5-16

ATEX	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	1.5-16

CSA	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	16-4

UL Recognized	
Nominal voltage UN	

Spring cage ground terminal block - ST 16-PE - 3036165

approvals

Nominal current IN	
mm ² /AWG/kcmil	16-4

VDE Gutachten mit Fertigungsüberwachung

Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	1.5-16

cUL Recognized

Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	16-4

GOST

LR

GL

Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	16

BV

DNV

RS



KR

NK

Spring cage ground terminal block - ST 16-PE - 3036165

approvals

IECEE CB Scheme	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	1.5-16



accessories

End cover

D-ST 16 - 3036657



Screwdriver tools

SZF 3-1,0X5,5 - 1206612



Labeled terminal marker

Spring cage ground terminal block - ST 16-PE - 3036165

accessories

WST 10/35 - 3030006



ZB 12 CUS - 0824942



ZB 12,LGS:L1-N,PE - 0812146



UC-TM 12 CUS - 0824613



UCT-TM 12 CUS - 0829630



ZBF 12 CUS - 0825018



Spring cage ground terminal block - ST 16-PE - 3036165

accessories

UC-TMF 12 CUS - 0824670



UCT-TMF 12 CUS - 0829686



Documentation

ST-IL - 3039900



Bridge

FBS 2-12 - 3005950



Mounting rail

NS 35/ 7,5 PERF 2000MM - 0801733



Spring cage ground terminal block - ST 16-PE - 3036165

accessories

NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



NS 35/ 7,5 WH UNPERF 2000MM - 1204122



NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



Spring cage ground terminal block - ST 16-PE - 3036165

accessories

NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



Terminal marking

ZB 12:UNPRINTED - 0812120



UC-TM 12 - 0819194



UCT-TM 12 - 0829144



Spring cage ground terminal block - ST 16-PE - 3036165

accessories

ZBF 12:UNBEDRUCKT - 0809735



UC-TMF 12 - 0819233



UCT-TMF 12 - 0829214



Drawings

Circuit diagram

