

# Feed-through terminal block - UK 2,5 N BU - 3003350

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Feed-through terminal block, Connection method: Screw connection, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 24 - 12, Width: 5.2 mm, Color: blue, Mounting type: NS 35/7,5, NS 35/15

## Product Features

- Universal foot which can be used on NS 35... and NS 32... DIN rails
- The UK universal screw terminal block series has the typical features which are decisive for practical applications
- Potential distribution via fixed bridges in the terminal center or insertion bridges in the clamping space



## Key commercial data

package_quantity	50
GTIN	4017918099282

## Technical data

### General

Number of levels	1
Number of connections	2
Color	blue
Insulating material	PA
Inflammability class according to UL 94	V2

### General

Maximum load current	24 A (with 2.5 mm <sup>2</sup> conductor cross section)
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I <sub>N</sub>	24 A
Nominal voltage U <sub>N</sub>	800 V
Open side panel	ja

### Dimensions

Width	5.2 mm
-------	--------

## Feed-through terminal block - UK 2,5 N BU - 3003350

### Technical data

#### Dimensions

Length	42.5 mm
Height NS 35/7,5	42 mm
Height NS 35/15	49.5 mm
Height NS 32	47 mm

#### Connection data

Connection in acc. with standard	IEC 60947-7-1
Connection method	Screw connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Min. AWG conductor cross section, stranded	24
Max. AWG conductor cross section, stranded	14
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm <sup>2</sup>
Conductor cross section stranded, with ferrule without plastic sleeve max.	2.5 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve max.	1.5 mm <sup>2</sup>
Cross section with insertion bridge, solid max.	2.5 mm <sup>2</sup>
Cross section with insertion bridge, stranded max.	2.5 mm <sup>2</sup>
2 conductors with same cross section, solid min.	0.2 mm <sup>2</sup>
2 conductors with same cross section, solid max.	1 mm <sup>2</sup>
2 conductors with same cross section, stranded min.	0.25 mm <sup>2</sup>
2 conductors with same cross section, stranded max.	1 mm <sup>2</sup>
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm <sup>2</sup>
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1.5 mm <sup>2</sup>
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.25 mm <sup>2</sup>
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	1 mm <sup>2</sup>
Cross section with insertion bridge, solid max.	2.5 mm <sup>2</sup>
Cross section with insertion bridge, stranded max.	2.5 mm <sup>2</sup>
Stripping length	7 mm
Internal cylindrical gage	A3
Screw thread	M3
Tightening torque, min	0.6 Nm

# Feed-through terminal block - UK 2,5 N BU - 3003350

## Technical data

### Connection data

<b>Tightening torque max</b>	0.8 Nm
------------------------------	--------

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27141120
<b>eCl@ss 4.1</b>	27141120
<b>eCl@ss 5.0</b>	27141120
<b>eCl@ss 5.1</b>	27141120
<b>eCl@ss 6.0</b>	27141120
<b>eCl@ss 7.0</b>	27141120
<b>eCl@ss 8.0</b>	27141120

### ETIM

<b>ETIM 2.0</b>	EC000897
<b>ETIM 3.0</b>	EC000897
<b>ETIM 4.0</b>	EC000897
<b>ETIM 5.0</b>	EC000897

### UNSPSC


<b>UNSPSC 6.01</b>	30211811
<b>UNSPSC 7.0901</b>	39121410
<b>UNSPSC 11</b>	39121410
<b>UNSPSC 12.01</b>	39121410
<b>UNSPSC 13.2</b>	39121410

## approvals

IECEX / ATEX / GL / CSA / UL Recognized / KEMA-KEUR / cUL Recognized / GOST / GL / DNV / CCA / IECCEB Scheme / LR / GOST / cULus Recognized /

### Approval details

<b>IECEX</b>	
Nominal voltage UN	550 V
Nominal current IN	22 A
mm <sup>2</sup> /AWG/kcmil	0.2-2.5



# Feed-through terminal block - UK 2,5 N BU - 3003350

## approvals

Nominal voltage UN	550 V
Nominal current IN	22 A
mm <sup>2</sup> /AWG/kcmil	0.2-2.5

**GL**

Nominal voltage UN	550 V
Nominal current IN	22 A
mm <sup>2</sup> /AWG/kcmil	2.5

**CSA**

Nominal voltage UN	300 V
Nominal current IN	20 A
mm <sup>2</sup> /AWG/kcmil	28-12

**UL Recognized**

Nominal voltage UN	300 V
Nominal current IN	20 A
mm <sup>2</sup> /AWG/kcmil	30-12

**KEMA-KEUR**

Nominal voltage UN	800 V
Nominal current IN	
mm <sup>2</sup> /AWG/kcmil	2.5

**cUL Recognized**

Nominal voltage UN	300 V
Nominal current IN	20 A
mm <sup>2</sup> /AWG/kcmil	30-12

# Feed-through terminal block - UK 2,5 N BU - 3003350

approvals

GOST

DNV

CCA	
Nominal voltage UN	800 V
Nominal current IN	
mm <sup>2</sup> /AWG/kcmil	2.5

IECEE CB Scheme	
Nominal voltage UN	800 V
Nominal current IN	
mm <sup>2</sup> /AWG/kcmil	2.5

LR

cULus Recognized

accessories

**End cover**

D-UK 2,5 BU - 3001103



## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

D-UK 2,5 - 3001022



---

### Warning label printed

WS 4- 5 - 0805344



WS 5- 5 - 0805331



WS 3- 5 - 0805357



---

### Mounting material

ZSR - 2303608



---

### Bridge

## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

FB-150 METER - 0201595



---

FBRI 20-5 N - 3000515



---

FBRI 16-5 N - 3000476



---

FBRI 12-5 N - 3000434



---

FBRI 2-5 N - 3000227



---

FBRI 10-5 N - 2770642



## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

---

FBRI 40-5 N - 3006823



EBL 3- 5 - 2303158



EBL 2- 5 - 2303145



EBL 10- 5 - 2303132



USBR 2-7 - 2303239





## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

USBRJ 2-7 - 2305538



---

SBRN 2-7 - 1413230



---

FB-150 METER - 0201595



---

### Short-circuit connector

KSS 5 - 2303543



---

### Test plug terminal block

RPS - 0201647



## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

MPS-MT - 0201744



---

### Partition plate

TS-KK 3 - 2770215



---

### Partition plate

ATP-UK - 3003224



---

### Terminal marking

SBS 5:UNBEDRUCKT - 1007219



ZB 5 :UNBEDRUCKT - 1050004



## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

UC-TM 5 - 0818108



---

UCT-TM 5 - 0828734



---

### Mounting rail

NS 32 PERF 2000MM - 1201002



---

NS 32 UNPERF 2000MM - 1201015



---

NS 35/ 7,5 PERF 2000MM - 0801733



## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

NS 35/ 7,5 UNPERF 2000MM - 0801681



---

NS 35/ 7,5 WH PERF 2000MM - 1204119



---

NS 35/ 7,5 WH UNPERF 2000MM - 1204122



---

NS 35/ 7,5 AL UNPERF 2000MM - 0801704



---

NS 35/ 7,5 ZN PERF 2000MM - 1206421



---

NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

---

NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



NS 35/15 PERF 2000MM - 1201730



NS 35/15 UNPERF 2000MM - 1201714



NS 35/15 WH PERF 2000MM - 0806602



## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

NS 35/15 WH UNPERF 2000MM - 1204135



NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 ZN PERF 2000MM - 1206599



NS 35/15 ZN UNPERF 2000MM - 1206586



NS 35/15 CU UNPERF 2000MM - 1201895



NS 35/15 CAP - 1206573



## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

---

NS 35/15-2,3 UNPERF 2000MM - 1201798



---

### Labeled terminal marker

ZB 5 CUS - 0824962



---

ZB 5,LGS:FORTL.ZAHLEN - 1050017



---

ZB 5,QR:FORTL.ZAHLEN - 1050020



---

ZB 5,LGS:GLEICHE ZAHLEN - 1050033



## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

ZB 5,LGS:L1-N,PE - 1050415



---

UC-TM 5 CUS - 0824581



---

UCT-TM 5 CUS - 0829595



---

### Insulating sleeve

MPS-IH WH - 0201663



---

MPS-IH RD - 0201676





## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

MPS-IH BU - 0201689



MPS-IH YE - 0201692



MPS-IH GN - 0201702



MPS-IH GY - 0201728



MPS-IH BK - 0201731



### End block

## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

CLIPFIX 35 - 3022218



CLIPFIX 35-5 - 3022276



E/NS 35 N - 0800886



E/UK - 1201442



E/UK 1 - 1201413



**Test socket**

## Feed-through terminal block - UK 2,5 N BU - 3003350

### accessories

PSBJ 3/13/4 - 0201304



PSB 3/10/4 - 0601292



### accessories

FBRI 19-5 N - 3000502

---

FBRI 18-5 N - 3000492

---

FBRI 17-5 N - 3000489

---


## Feed-through terminal block - UK 2,5 N BU - 3003350

accessories

FBRI 15-5 N - 3000463

---

FBRI 14-5 N - 3000450



FBRI 13-5 N - 3000447



FBRI 11-5 N - 3000421

---

### Drawings

Circuit diagram

