

Micro terminal - MT 1,5 - 3100305

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Micro terminal, Connection method: Screw connection, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 16, Width: 4.2 mm, Color: gray, Mounting type: NS 15

Product Features

- Nominal cross section of 1.5 mm²
- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Clear arrangement thanks to marking of all terminal points
- Easy potential distribution thanks to standardized plug-in bridges
- Design width of just 4.2 mm
- Wide range of labeling options
- Can be bridged in terminal center
- Snap-on foot for NS 15 DIN rails

Key commercial data

package_quantity	50
GTIN	4017918099251

Technical data

General

Number of levels	1
Number of connections	2
Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0

General

Maximum load current	17.5 A (with 1.5 mm ² conductor cross section)
Rated surge voltage	4 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I _N	17.5 A
Nominal voltage U _N	400 V
Open side panel	ja

Micro terminal - MT 1,5 - 3100305

Technical data

Dimensions

Width	4.2 mm
Length	22 mm
Height NS 15	23.5 mm

Connection data

Connection in acc. with standard	IEC 60947-7-1
Connection method	Screw connection
Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	16
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Min. AWG conductor cross section, stranded	26
Max. AWG conductor cross section, stranded	16
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	0.75 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	0.75 mm ²
2 conductors with same cross section, solid min.	0.14 mm ²
2 conductors with same cross section, solid max.	0.5 mm ²
2 conductors with same cross section, stranded min.	0.14 mm ²
2 conductors with same cross section, stranded max.	0.5 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.25 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	0.34 mm ²
Stripping length	6 mm
Internal cylindrical gage	A 1
Screw thread	M2
Tightening torque, min	0.22 Nm
Tightening torque max	0.25 Nm

classifications

eCl@ss

eCl@ss 4.0	27141123
eCl@ss 4.1	27141123
eCl@ss 5.0	27141120
eCl@ss 5.1	27141120

Micro terminal - MT 1,5 - 3100305

classifications

eCl@ss

eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141120

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897
ETIM 5.0	EC000897

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

CSA / UL Recognized / KEMA-KEUR / GOST / LR / GL / BV / DNV / CCA / GOST /

Approval details

Nominal voltage UN	300 V
Nominal current IN	15 A
mm ² /AWG/kcmil	28-14

Nominal voltage UN	300 V
Nominal current IN	15 A
mm ² /AWG/kcmil	30-14

--	--

Micro terminal - MT 1,5 - 3100305

approvals

Nominal voltage UN	400 V
Nominal current IN	
mm ² /AWG/kcmil	1.5



LR


GL

BV

DNV

CCA

Nominal voltage UN	400 V
Nominal current IN	
mm ² /AWG/kcmil	1.5



accessories

End cover

D-MT 1,5 - 3100321



Screwdriver tools

Micro terminal - MT 1,5 - 3100305

accessories

SZS 0,4X2,5 VDE - 1205037



Bridge

FBRN 4-4 N - 3001569



FBRN 5-4 N - 3001572



FBRN 6-4 N - 3001585



FBRN 7-4 N - 3001598



Micro terminal - MT 1,5 - 3100305

accessories

FBRN 8-4 N - 3001608



FBRN 10-4 N - 3001624



FBRN 20-4 N - 3001637



Mounting rail

NS 15 UNPERF 2000MM - 1401695



NS 15 PERF 2000MM - 1401682



Micro terminal - MT 1,5 - 3100305

accessories

NS 15 AL PERF 2000MM - 1401763



NS 15 WH PERF 2000MM - 1204096



Terminal marking

ZBF 4:UNBEDRUCKT - 0808587



UC-TMF 4 - 0818166



UCT-TMF 4 - 0828742



Labeled terminal marker

Micro terminal - MT 1,5 - 3100305

accessories

ZBF 4 CUS - 0825023



ZBF 4,LGS:FORTL.ZAHLEN - 0808626



ZBF 4,QR:FORTL.ZAHLEN - 0808820



ZBF 4,LGS:GERADE ZAHLEN - 0810818



ZBF 4,LGS:UNGERADE ZAHLEN - 0810850



UC-TMF 4 CUS - 0824630



Micro terminal - MT 1,5 - 3100305

accessories

UCT-TMF 4 CUS - 0829651



End block

E/MBK - 1401637



E/MK - 1421633



E/MK 1 - 1421659



CLIPFIX 15 - 3022263



Micro terminal - MT 1,5 - 3100305

accessories

FBRN 9-4 N - 3001611

Drawings

Circuit diagram



© Phoenix Contact 2014 - all rights reserved
<http://www.phoenixcontact.com>