

# Marker for terminal blocks - UCT1-TM 5 - 0829482

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



UniCard materials for thermal transfer printer, for labeling Weidmüller, Conta Clip, and Klemsan terminal blocks, 72-section, can be labeled with THERMOMARK CARD and BLUEMARK LED, color: white

The figure shows the UCT-TM 5 version

## Product Features

- The UCT1-TM ... UniCard labeling range includes markers for Weidmüller, Conta-Clip, and Klemsan terminal blocks
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements

## Key commercial data

<b>package_quantity</b>	10
<b>GTIN</b>	4046356571104

## Technical data

### Dimensions

<b>Length (b)</b>	10 mm
<b>Height</b>	3.48 mm
<b>Width (a)</b>	2 mm

### Ambient conditions

<b>Ambient temperature (operation)</b>	-40 °C ... 120 °C
--	-------------------

### General

<b>Note</b>	Can be labeled via thermal transfer
<b>Color</b>	white
<b>Components</b>	free from silicone and halogen
<b>Inflammability class according to UL 94</b>	V0
<b>Material</b>	PC
<b>Material</b>	PC
<b>Wipe resistance</b>	DIN EN 61010-1 (VDE 0411-1)
<b>Number of individual labels</b>	72
<b>Number of individual labels per row</b>	12
<b>RoHS compliant</b>	Yes
<b>Printability</b>	Thermal transfer
<b>Printability</b>	Inkjet printing

# Marker for terminal blocks - UCT1-TM 5 - 0829482

## Technical data

### General

<b>Test for substances that would hinder coating with paint or varnish</b>	VW PV 3.10.7:2005-02
<b>Result</b>	Test passed
<b>Test specification weathering-resistance</b>	Following ISO 4892-2:2013-03
<b>Test duration</b>	96 h
<b>Wipe resistance test result</b>	Test passed
<b>Salt spray test specification</b>	DIN EN 60068-2-11:2000-02
<b>Test duration</b>	96 min
<b>Salt spray testing result</b>	Test passed
<b>Alternating condensation climate with SO2 test specification</b>	DIN 50018:2013-05
<b>Climate level</b>	AHT 1.0 S
<b>Cycles</b>	2
<b>Condensation test result</b>	Test passed
<b>Wipe resistance of test specification inscriptions</b>	DIN EN 61010-1 (VDE 0411-1):2011-07
<b>Result</b>	Test passed
<b>Marking mounting type</b>	Snap into tall marker groove

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	24190219
<b>eCl@ss 4.1</b>	24190219
<b>eCl@ss 5.0</b>	27141137
<b>eCl@ss 5.1</b>	27141137
<b>eCl@ss 6.0</b>	27141137
<b>eCl@ss 7.0</b>	27141137
<b>eCl@ss 8.0</b>	27141137

### ETIM

<b>ETIM 2.0</b>	EC000761
<b>ETIM 3.0</b>	EC000761
<b>ETIM 4.0</b>	EC000761
<b>ETIM 5.0</b>	EC000761

### UNSPSC

<b>UNSPSC 6.01</b>	30211811
<b>UNSPSC 7.0901</b>	39121410
<b>UNSPSC 11</b>	39121410
<b>UNSPSC 12.01</b>	39121410
<b>UNSPSC 13.2</b>	39121410

## Marker for terminal blocks - UCT1-TM 5 - 0829482

accessories

### **Magazine**

THERMOMARK CARD-UCT-MAG1 - 5146480



---

### Drawings

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>