

# Snap-in markers - US-EMP (29X8) - 0829436

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Snap-in markers, Card, white, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: snapped into marker carrier, Lettering field: 29 x 8 mm

The illustration shows a version of the product

## Product Features

- The US-EMP ... UniSheet labeling range includes markers that can be fitted into existing CARRIER EMP ... label frames
- The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The perforated markers are easy to separate and can be easily fitted
- The sheets provide space for including function texts

## Key commercial data

<b>package_quantity</b>	10
<b>GTIN</b>	4046356562232

## Technical data

### Dimensions

<b>Length (b)</b>	29 mm
<b>Height</b>	0.3 mm
<b>Width (a)</b>	8 mm

### Ambient conditions

<b>Ambient temperature (operation)</b>	-30 °C ... 80 °C
<b>Recommended storage conditions</b>	10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended.

### General

<b>Color</b>	white
<b>Components</b>	Silicone-free
<b>Inflammability class according to UL 94</b>	V0
<b>Material</b>	PVC
<b>Wipe resistance</b>	DIN EN 61010-1 (VDE 0411-1)
<b>Number of individual labels</b>	48
<b>Number of individual labels per row</b>	3
<b>RoHS compliant</b>	Yes
<b>Printability</b>	Thermal transfer

# Snap-in markers - US-EMP (29X8) - 0829436

## Technical data

### General

<b>Test for substances that would hinder coating with paint or varnish</b>	VW PV 3.10.7:2005-02
<b>Result</b>	Test passed
<b>Test specification weathering-resistance</b>	Following ISO 4892-2:2013-03
<b>Test duration</b>	96 h
<b>Wipe resistance test result</b>	Test passed
<b>Salt spray test specification</b>	DIN EN 60068-2-11:2000-02
<b>Test duration</b>	96 h
<b>Salt spray testing result</b>	Test passed
<b>Alternating condensation climate with SO2 test specification</b>	Following DIN 50018:2013-05
<b>Climate level</b>	AHT 1.0 S
<b>Cycles</b>	2
<b>Condensation test result</b>	Test passed
<b>Wipe resistance of test specification inscriptions</b>	IEC 61010-1:2010-06
<b>Result</b>	Test passed
<b>Foil strength</b>	300 µm
<b>Marking mounting type</b>	snapped into marker carrier

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	24190219
<b>eCl@ss 4.1</b>	24190219
<b>eCl@ss 5.0</b>	27141137
<b>eCl@ss 5.1</b>	27141137
<b>eCl@ss 6.0</b>	27141137
<b>eCl@ss 7.0</b>	27141137
<b>eCl@ss 8.0</b>	27141137

### ETIM

<b>ETIM 2.0</b>	EC000761
<b>ETIM 3.0</b>	EC000761
<b>ETIM 4.0</b>	EC001694
<b>ETIM 5.0</b>	EC001694

### UNSPSC

<b>UNSPSC 6.01</b>	30211811
<b>UNSPSC 7.0901</b>	39121410
<b>UNSPSC 11</b>	39121410
<b>UNSPSC 12.01</b>	39121410
<b>UNSPSC 13.2</b>	39121410

## Snap-in markers - US-EMP (29X8) - 0829436

accessories

### Magazine

THERMOMARK CARD-US-MAG1 - 5146451



---

### Drawings

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>