

# Plastic label - US-EMLP (17X7) - 0828792

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Plastic label, Card, white, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: Adhesive, Lettering field: 17 x 7 mm

The figure shows the US-EMLP (20x9) version

## Product Features

- The US-EMLP ... UniSheet labeling range includes self-adhesive device markers with good adhesive properties
- The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The perforated markers are easy to separate and can be easily fitted
- The sheets provide space for including function texts

## Key commercial data

<b>package_quantity</b>	10
<b>GTIN</b>	4046356558730

## Technical data

### Dimensions

<b>Length (b)</b>	17 mm
<b>Height</b>	0.5 mm
<b>Width (a)</b>	7 mm

### Ambient conditions

<b>Ambient temperature (operation)</b>	-30 °C ... 80 °C
<b>Ambient temperature (assembly)</b>	15 °C ... 25 °C

### General

<b>Color</b>	white
<b>Components</b>	Silicone-free
<b>Inflammability class according to UL 94</b>	V0
<b>Material</b>	PVC
<b>Wipe resistance</b>	DIN EN 61010-1 (VDE 0411-1)
<b>Number of individual labels</b>	114
<b>Number of individual labels per row</b>	6
<b>RoHS compliant</b>	Yes
<b>Adhesive</b>	Acrylic
<b>Printability</b>	Thermal transfer

# Plastic label - US-EMLP (17X7) - 0828792

## Technical data

### General

<b>Test specification weathering-resistance</b>	Following ISO 4892-2:2013-03
<b>Test duration</b>	96 h
<b>Wipe resistance test result</b>	Test passed
<b>Salt spray test specification</b>	DIN EN ISO 9227:2012-09
<b>Test duration</b>	96 h
<b>Salt spray testing result</b>	Test passed
<b>Alternating condensation climate with SO2 test specification</b>	DIN 50018:2013-05
<b>Climate level</b>	AHT 1.0 S
<b>Cycles</b>	2
<b>Condensation test result</b>	Test passed
<b>Wipe resistance of test specification inscriptions</b>	IEC 61010-1:2010-06
<b>Result</b>	Test passed
<b>Burning behaviour</b>	self-extinguishing
<b>Foil strength</b>	500 µm
<b>Adhesive strength</b>	50 µm
<b>Marking mounting type</b>	Adhesive

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	24190219
<b>eCl@ss 4.1</b>	24190219
<b>eCl@ss 5.0</b>	27141137
<b>eCl@ss 5.1</b>	27141137
<b>eCl@ss 6.0</b>	27141137
<b>eCl@ss 7.0</b>	27141137
<b>eCl@ss 8.0</b>	27141137

### ETIM

<b>ETIM 2.0</b>	EC000761
<b>ETIM 3.0</b>	EC000761
<b>ETIM 4.0</b>	EC000761
<b>ETIM 5.0</b>	EC000761

### UNSPSC

<b>UNSPSC 6.01</b>	30211811
<b>UNSPSC 7.0901</b>	39121410
<b>UNSPSC 11</b>	39121410
<b>UNSPSC 12.01</b>	39121410
<b>UNSPSC 13.2</b>	39121410

## Plastic label - US-EMLP (17X7) - 0828792

accessories

### Magazine

THERMOMARK CARD-US-MAG1 - 5146451



---

### Drawings

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>