

# Screwdriver - SZS 0,5X3,0 VDE - 1207404

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screwdriver, slot-headed, VDE insulated, size: 0.5 x 3.0 x 100 mm, 2-component grip, with non-slip grip

The illustration shows version SZS 0,6 x 3,5

## Product Features

- The tools feature ergonomic two-component safety handles
- Large contact surface of blades inside screw head
- Individually tested safety screwdrivers according to DIN EN 60900 (VDE 0682-201)
- For working on or in the vicinity of live parts up to 1000 V AC or 1500 V DC

## Key commercial data

<b>package_quantity</b>	10
<b>GTIN</b>	4017918572525

## Technical data

### Dimensions

<b>Length (b)</b>	181 mm
<b>Width (a)</b>	26 mm
<b>Blade thickness</b>	5 mm
<b>Blade width</b>	3 mm
<b>Blade height</b>	100 mm

### General

<b>Type</b>	Bladed
<b>Material</b>	Alloyed tool steel
<b>Test standard</b>	DIN/ISO 2380-1 IEC 60900:2004

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	21040401
<b>eCl@ss 4.1</b>	21040401
<b>eCl@ss 5.0</b>	21040401
<b>eCl@ss 5.1</b>	21040401
<b>eCl@ss 6.0</b>	21040401

# Screwdriver - SZS 0,5X3,0 VDE - 1207404

## classifications

### eCl@ss

eCl@ss 7.0	21040409
eCl@ss 8.0	21040409

### ETIM

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158
ETIM 5.0	EC000158

### UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

## approvals

VDE Zeichengenehmigung / GOST / GOST /

### Approval details

VDE Zeichengenehmigung

GOST

## Drawings

## Screwdriver - SZS 0,5X3,0 VDE - 1207404

Pictogram

