

Double-level terminal block - UKK 5 - 2774017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Double-level terminal block, Cross section: 0.2 mm² - 4 mm², AWG: 24 - 12, Connection type: Screw connection, Width: 6.2 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15, NS 32

Product Features

- Large-surface labeling option

Key commercial data

package_quantity	50
GTIN	4017918068301

Technical data

General

Number of levels	2
Number of connections	4
Color	gray
Insulating material	PA
Inflammability class according to UL 94	V0

General

Rated surge voltage	6 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I _N	32 A
Nominal voltage U _N	500 V
Open side panel	ja
Temperature-rise test	Test passed

Dimensions

Width	6.2 mm
Length	56 mm
Height NS 35/7,5	62 mm
Height NS 35/15	69.5 mm
Height NS 32	67 mm

Double-level terminal block - UKK 5 - 2774017

Technical data

Connection data

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule without plastic sleeve max.	4 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section stranded, with ferrule with plastic sleeve max.	2.5 mm ²
Cross section with insertion bridge, solid max.	4 mm ²
Cross section with insertion bridge, stranded max.	2.5 mm ²
2 conductors with same cross section, solid min.	0.2 mm ²
2 conductors with same cross section, solid max.	1.5 mm ²
2 conductors with same cross section, stranded min.	0.2 mm ²
2 conductors with same cross section, stranded max.	1.5 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.25 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	1.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1.5 mm ²
Cross section with insertion bridge, solid max.	4 mm ²
Cross section with insertion bridge, stranded max.	2.5 mm ²
Stripping length	8 mm
Screw thread	M3
Tightening torque, min	0.6 Nm
Tightening torque max	0.8 Nm

classifications

eCl@ss

eCl@ss 4.0	27141118
eCl@ss 4.1	27141118
eCl@ss 5.0	27141118
eCl@ss 5.1	27141118
eCl@ss 6.0	27141120

Double-level terminal block - UKK 5 - 2774017

classifications

eCl@ss

eCl@ss 7.0	27141120
eCl@ss 8.0	27141120

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897
ETIM 5.0	EC000897

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

approvals

CSA / UL Recognized / KEMA-KEUR / cUL Recognized / GL / DNV / RS / PRS / CCA / cULus Recognized /

Approval details

Usegroups	B	C
Nominal voltage UN	300 V	300 V
Nominal current IN	25 A	25 A
mm ² /AWG/kcmil	28-10	28-10

Nominal voltage UN	600 V
Nominal current IN	30 A
mm ² /AWG/kcmil	26-10

Nominal voltage UN	500 V

Double-level terminal block - UKK 5 - 2774017

approvals

Nominal current IN	32 A
mm ² /AWG/kcmil	4

cUL Recognized	
Nominal voltage UN	600 V
Nominal current IN	30 A
mm ² /AWG/kcmil	26-10

GL

DNV

RS

PRS

CCA	
Nominal voltage UN	500 V
Nominal current IN	
mm ² /AWG/kcmil	4

cULus Recognized	
-------------------------	--

accessories

Partition plate

DP-UKK 3/5 - 2770794



Double-level terminal block - UKK 5 - 2774017

accessories

TS-KK 3 - 2770215



End cover

DG-UKK 3/5 - 2770817



D-UKK 3/5 - 2770024



Warning label printed

WS 5- 6 - 1004403



WS 4- 6 - 1004209



Double-level terminal block - UKK 5 - 2774017

accessories

WS 3- 6 - 1004115



Bridge

FB-150 METER - 0201595



ISSBI 10- 6 - 0301505



LB 10-6 BU - 0202280



LB 10-6 RD - 0202293



Double-level terminal block - UKK 5 - 2774017

accessories

LB 10-6 GY - 0202358



LB 100-6 GY - 0202345



LB 100-6 RD - 0202316



LB 100-6 BU - 0202303



FBI 10- 6 - 0203250



FBI 20- 6 - 0201867



Double-level terminal block - UKK 5 - 2774017

accessories

FBI 100- 6 - 0201650



EB 2- 6 - 0201155



EB 3- 6 - 0201142



EB 10- 6 - 0201139



SBRN 2-7 - 1413230



Double-level terminal block - UKK 5 - 2774017

accessories

USBR 2-7 - 2303239



USBRJ 2-7 - 2305538



Short-circuit connector

KSS 3-6 - 0309523



KSS 6 - 0301547



Test plug terminal block

PS-UKK 5 - 3000625



Double-level terminal block - UKK 5 - 2774017

accessories

PS-UKK/E - 3000641



RPS - 0201647



Partition plate

ATP-UKK 3/5 - 2778521



Terminal marking

SBS 6:UNBEDRUCKT - 1007222



ZB 6:UNBEDRUCKT - 1051003



Double-level terminal block - UKK 5 - 2774017

accessories

UC-TM 6 - 0818085



UCT-TM 6 - 0828736



Insulating sleeve

IS-K 4 - 1302338



Mounting rail

NS 32 PERF 2000MM - 1201002



NS 32 UNPERF 2000MM - 1201015



Double-level terminal block - UKK 5 - 2774017

accessories

NS 35/ 7,5 PERF 2000MM - 0801733



NS 35/ 7,5 UNPERF 2000MM - 0801681



NS 35/ 7,5 WH PERF 2000MM - 1204119



NS 35/ 7,5 WH UNPERF 2000MM - 1204122



NS 35/ 7,5 AL UNPERF 2000MM - 0801704



NS 35/ 7,5 ZN PERF 2000MM - 1206421



Double-level terminal block - UKK 5 - 2774017

accessories

NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



NS 35/15 PERF 2000MM - 1201730



NS 35/15 UNPERF 2000MM - 1201714



Double-level terminal block - UKK 5 - 2774017

accessories

NS 35/15 WH PERF 2000MM - 0806602



NS 35/15 WH UNPERF 2000MM - 1204135



NS 35/15 AL UNPERF 2000MM - 1201756



NS 35/15 ZN PERF 2000MM - 1206599



NS 35/15 ZN UNPERF 2000MM - 1206586



NS 35/15 CU UNPERF 2000MM - 1201895



Double-level terminal block - UKK 5 - 2774017

accessories

NS 35/15 CAP - 1206573



NS 35/15-2,3 UNPERF 2000MM - 1201798



Labeled terminal marker

ZB 6 CUS - 0824992



ZB 6,LGS:FORTL.ZAHLEN - 1051016



ZB 6,QR:FORTL.ZAHLEN - 1051029



Double-level terminal block - UKK 5 - 2774017

accessories

ZB 6,LGS:GLEICHE ZAHLEN - 1051032



ZB 6,LGS:L1-N,PE - 1051414



ZB 6,LGS:U-N - 1051430



UC-TM 6 CUS - 0824589



UCT-TM 6 CUS - 0829602



End block

Double-level terminal block - UKK 5 - 2774017

accessories

CLIPFIX 35 - 3022218



CLIPFIX 35-5 - 3022276



E/NS 35 N - 0800886



E/UK - 1201442



E/UK 1 - 1201413



Test socket

Double-level terminal block - UKK 5 - 2774017

accessories

PSBJ 3/13/4 - 0201304



PSB 3/10/4 - 0601292



Drawings

Circuit diagram

