

## Connector - BNC-V 75 - 2805070

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



BNC connector, single-level, for mounting on NS 32 or NS 35/7.5, wave impedance: 75 Ohm

### Product Features

- Can be labeled individually
- With isolated structure on the DIN rail
- For coaxial cables
- DIN rail-mountable and can be aligned

### Key commercial data

|                         |               |
|-------------------------|---------------|
| <b>package_quantity</b> | 10            |
| <b>GTIN</b>             | 4017918074562 |

### Technical data

#### Dimensions

|               |         |
|---------------|---------|
| <b>Height</b> | 58.8 mm |
| <b>Width</b>  | 22 mm   |
| <b>Length</b> | 42.5 mm |

#### Ambient conditions

|  |        |
|--|--------|
| <b>Ambient temperature (operation)</b> | 125 °C |
| <b>Degree of protection</b>            | IP20   |

#### General

|  |           |
|--|-----------|
| <b>Housing material</b>                        | PA        |
| <b>Inflammability class according to UL 94</b> | V2        |
| <b>Color</b>                                   | gray      |
| <b>Mounting type</b>                           | NS 35/7,5 |

#### Protective circuit

|   |                 |
|---|-----------------|
| <b>Frequency range</b>                          | 0 GHz ... 3 GHz |
| <b>Standing wave ratio SWR in a 75 Ω system</b> | < 1.1 (3 GHz)   |

#### Connection data

|                          |          |
|--------------------------|----------|
| <b>Connection method</b> | BNC 75 Ω |
|--------------------------|----------|

# Connector - BNC-V 75 - 2805070

## classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141131 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002498 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211802 |
| UNSPSC 7.0901 | 39121402 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121404 |
| UNSPSC 13.2   | 39121404 |

## approvals

GOST /

### Approval details



## accessories

### Mounting rail

NS 35/ 7,5 PERF 2000MM - 0801733



## Connector - BNC-V 75 - 2805070

### accessories

NS 35/ 7,5 UNPERF 2000MM - 0801681



---

NS 35/ 7,5 WH PERF 2000MM - 1204119



---

NS 35/ 7,5 WH UNPERF 2000MM - 1204122



---

NS 35/ 7,5 AL UNPERF 2000MM - 0801704



---

NS 35/ 7,5 ZN PERF 2000MM - 1206421



---

NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



## Connector - BNC-V 75 - 2805070

accessories

---

NS 35/ 7,5 CU UNPERF 2000MM - 0801762



NS 35/ 7,5 CAP - 1206560



### Drawings

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>