

Shield connection terminal block - SK 20 - 3025189

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Shield connection clamp, for shield on busbars, contact resistance < 1 mOhm

Product Features

- Easy handling
- Spring-loaded, large-surface pressure plate
- Suitable for direct and busbar mounting
- Knurled screw

Key commercial data

package_quantity	10
GTIN	4017918130312

Technical data

General

Number of levels	1
Number of connections	1
Color	silver

Dimensions

Length	19.5 mm
Width	24 mm
Height	75.00 mm

Connection data

Screw thread	M4
Tightening torque max	0.8 Nm
Connection method	Screwing on

classifications

eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141131

Shield connection terminal block - SK 20 - 3025189

classifications

eCl@ss

eCl@ss 6.0	27141150
eCl@ss 7.0	27141150
eCl@ss 8.0	27141150

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002020
ETIM 5.0	EC002020

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

accessories

Support

AB-SK - 3025341



AB/SS - 0404428



Pick-off terminal block

AK 4 - 0404017



Shield connection terminal block - SK 20 - 3025189

accessories

Installation terminal block

AKG 4 GNYE - 0421029



AKG 4 BK - 0421032



Neutral conductor rail


NLS-CU 3/10 SN 1000MM - 0402174



Drawings


Shield connection terminal block - SK 20 - 3025189

Diagram



Shield connection terminal block - SK 20 - 3025189

Dimensioned drawing



Dimensioned drawing