

Base strip - PC 6-16/ 2-G1-10,16 - 1998933

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Header, Nominal current: 76 A, Rated voltage (III/2): 1000 V, Number of positions: 2, Pitch: 10.16 mm, Color: green, Contact surface: Silver, Assembly: Soldering

The figure shows a 5-pos. version of the product

Product Features

- PCB/PCB connections by using IPC 16 headers
- PCB-SHIELD shroud for a professional EMC shield connection
- PC 6-16 headers for use in combination with all PC 6 and PC 16 plugs

Key commercial data

package_quantity	50
GTIN	4046356038430

Technical data

Dimensions

Length	34 mm
Height	13.4 mm
Pitch	10.16 mm
Dimension a	10.16 mm
Pin dimensions	1 x 1.2 mm
Pin spacing	10.16 mm
Hole diameter	1.7 mm

General

Range of articles	PC 6-16/..-G1
Insulating material group	I
Rated surge voltage (III/3)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (II/2)	6 kV
Rated voltage (III/3)	1000 V
Rated voltage (III/2)	1000 V
Rated voltage (II/2)	1000 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	76 A (41 A in combination with PC 6 plug)
Maximum load current	76 A (41 A in combination with PC 6 plug)

Base strip - PC 6-16/ 2-G1-10,16 - 1998933

Technical data

General

Insulating material	PA
Inflammability class according to UL 94	V0
Color	green
Number of positions	2

classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637


UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

approvals

UL Recognized / SEV / cUL Recognized / CCA / IECCE CB Scheme / GOST / GOST / cULus Recognized /

Approval details

UL Recognized 			
Usegroups	B	C	D
Nominal voltage UN	300 V	300 V	600 V
Nominal current IN	66 A	66 A	5 A
mm ² /AWG/kcmil			

Base strip - PC 6-16/ 2-G1-10,16 - 1998933

approvals

SEV	
Nominal voltage UN	1000 V
Nominal current IN	76 A
mm ² /AWG/kcmil	

cUL Recognized			
Usegroups	B	C	D
Nominal voltage UN	300 V	300 V	600 V
Nominal current IN	66 A	66 A	5 A
mm ² /AWG/kcmil			

CCA	
Nominal voltage UN	1000 V
Nominal current IN	76 A
mm ² /AWG/kcmil	

IECEE CB Scheme	
Nominal voltage UN	1000 V
Nominal current IN	76 A
mm ² /AWG/kcmil	

GOST	

cULus Recognized	

accessories

Coding element

Base strip - PC 6-16/ 2-G1-10,16 - 1998933

accessories

CP-PC RD - 1701967



CS-IPC 16/ 6 - 1970016




accessories

SK 10/5: 0-9 - 0804688

Drawings


Base strip - PC 6-16/ 2-G1-10,16 - 1998933

Drilling diagram



Base strip - PC 6-16/ 2-G1-10,16 - 1998933

Diagram



Type: PC 16/...-ST-10,16 with PC 6-16/...-G1-10,16

Dimensioned drawing

