

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.735

Date : Mar 18, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7715.735

created : 18.03.2014 on www.rittal.com/com-en



Product description

Description:

- Wall-mounted enclosure with optimum accessibility thanks to hinged part.

Material:

- Wall and hinged part: Sheet steel, 1.5 mm
- Viewing window: Single-pane safety glass, 3 mm

Surface finish:

- powder-coated

Colour:

- Wall and hinged part: RAL 7035
- Glazed door: RAL 7035/7015 (slate grey)

Supply includes:

- Wall section
- Hinged part with 25 mm pitch pattern of holes in the front and rear frame
- Designer glazed door
- Wall section: Gland plate, solid, top
- Mini-comfort handle
- 4 wall mounting brackets 10 mm
- Earth rail with star earthing
- Hinged part: Side outlet filters left and right
- Hinged part with two 482.6 mm (19") mounting angles, fully depth adjustable
- Wall section: C rail mounted horizontally for cable clamping
- Wall section: 2 vertical punched rails
- Wall section: Gland plate with brush strip, bottom
- Security lock 3524 E

Note:

- Protection category IP 54 in conjunction with solid gland plate, top and bottom
- Enclosure 673 mm deep with reinforced wall mounting bracket

Packs of:

- 1 pc(s).

EAN:

- 4028177324244

Customs tariff number:

- 94032080

Product features**Design:**

- Pre-configured

Dimensions:

- Width: 600 mm
- Height: 746 mm
- Depth: 573 mm

Depth hinged part:

- 416 mm

Installation depth:

- 520 mm

Clearances:

- Clearance width: 502 mm
- Clearance height: 683 mm


Wall section:

- Depth: 135 mm

Load capacity:

- Hinged part, static (max.): 75 kg


Approvals**Approvals:**

-  [UL + C-UL \(EN\)](#)

Downloads**Data sheets:**

-  [Technical details \(EN\)](#)

Documentation:

-  [Instructions \(EN, DE\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP