## Rittal - The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part with punched rails and mounting angles, depth-variable – DK 7712.135

Date: Mar 18, 2014



## Wall-mounted enclosures EL, 3-part with punched rails and mounting angles, depth-variable – DK 7712.135

created: 18.03.2014 on www.rittal.com/com-en



#### **Product description**

#### **Description:**

• Wall-mounted enclosure with optimum accessibility thanks to hinged part.

#### Material:

- Wall and hinged part: Sheet steel, 1.5 mm
- Viewing window: Single-pane safety glass, 3 mm

#### Surface finish:

powder-coated

#### Colour:

- Wall and hinged part: RAL 7035
- Glazed door: RAL 7035/7015 (slate grey)

#### Protection category

IP to IEC 60 529:

• IP 55

#### Supply includes:

- Wall section
- Hinged part with 25 mm pitch pattern of holes in the front and rear frame
- Designer glazed door
- Wall section: Gland plate, solid, top and bottom
- Wall section: 2 vertical punched rails
- Wall section: C rail mounted horizontally for cable clamping
- Hinged part with two 482.6 mm (19") mounting angles, fully depth adjustable

1

- 4 wall mounting brackets 10 mm
- Mini-comfort handle
- Security lock 3524 E

#### Packs of:

• 1 pc(s).

#### EAN:

© Rittal 2013

Customs	tariff
number	

• 94032080

#### **Product features**

#### Design:

• with punched rails and mounting angles, depth-variable

#### **Dimensions:**

Width: 600 mmHeight: 612 mmDepth: 473 mm

#### Depth hinged part:

• 316 mm

#### Installation depth:

• 420 mm

#### Clearances:

Clearance width: 502 mmClearance height: 549 mm

#### Wall section:

• Depth: 135 mm

#### Load capacity:

• Hinged part, static (max.): 60 kg

#### **Approvals**

#### Approvals:

• 🔁 <u>UL + C-UL (EN)</u>

#### **Downloads**

#### Data sheets:

• Technical details (EN)

#### Documentation:

• 🔁 Instructions (EN, DE)

© Rittal 2013

2

# Rittal – The System.

### Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postfach 1662 · D-35726 Herborn Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

> IT INFRASTRUCTURE

SOFTWARE & SERVICES



>> CLIMATE CONTROL