

# Rittal – The System.

Faster – better – everywhere.

## ► Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2246.605

Date : Mar 18, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2246.605

created : 18.03.2014 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

### Description:

- Wall-mounted enclosure with optimum accessibility thanks to hinged part.

### Material:

- Wall and hinged part: Sheet steel, 1.5 mm
- Viewing window: Single-pane safety glass, 3 mm

### Surface finish:

- powder-coated

### Colour:

- Wall and hinged part: RAL 7035
- Glazed door: RAL 7035/7015 (slate grey)

### Protection category IP to IEC 60 529:

- IP 55

### Supply includes:

- Wall section
- Hinged part with 25 mm pitch pattern of holes in the front and rear frame
- Designer glazed door
- Wall section: Gland plate, solid, top and bottom
- Wall section: Mounting plate supplied loose
- Hinged part with two 482.6 mm (19") mounting angles
- Mini-comfort handle
- Security lock 3524 E

### Packs of:

- 1 pc(s).

### EAN:

- 4028177324312

Customs tariff  
number:

- 94032080

## Product features

Design:

- with mounting plate and mounting angles, static installation

Dimensions:

- Width: 600 mm
- Height: 345 mm
- Depth: 373 mm

Depth hinged part:

- 216 mm

Installation depth:

- 320 mm

Clearances:

- Clearance width: 502 mm
- Clearance height: 282 mm

Mounting plate:

- Width: 485 mm
- Height: 299 mm

Wall section:

- Depth: 135 mm

Load capacity:




- Hinged part, static (max.): 30 kg

Weight:

- 27.1 kg

## Approvals

Approvals:


-  [Lloyds Register of Shipping \(EN\)](#)
-  [UL + C-UL \(EN\)](#)
-  [Germanischer Lloyd \(EN\)](#)

## Downloads

Data sheets:

-  [Technical details \(EN\)](#)

Documentation:

-  [Instructions \(EN, DE\)](#)

# Rittal – The System.

---

**Faster – better – everywhere.**

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG  
Postfach 1662 · D-35726 Herborn  
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319  
E-Mail: [info@rittal.com](mailto:info@rittal.com) · [www.rittal.com](http://www.rittal.com)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP