Rittal – The System.

Faster – better – everywhere.

Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2249.605

Date : Mar 18, 2014



ENCLOSURES

DISTRIBUTION >> CLIMATE CONTROL

FRIEDHELM LOH GROUP

Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2249.605 created : 18.03.2014 on www.rittal.com/com-en



Product description

Description: • Wall-mounted enclosure with optimum accessibility thanks to hinged part. Material: • Wall and hinged part: Sheet steel, 1.5 mm • Viewing window: Single-pane safety glass, 3 mm Surface finish: • powder-coated Colour: • Wall and hinged part: RAL 7035 • Glazed door: RAL 7035/7015 (slate grey) Protection category IP to IEC 60 529: • IP 55 Supply includes: • Wall section • Hinged part with 25 mm pitch pattern of holes in the front and rear frame • Designer glazed door • Wall section: Gland plate, solid, top and bottom • Wall section: Mounting plate supplied loose • Hinged part with two 482.6 mm (19") mounting angles • Mini-comfort handle • Security lock 3524 E Packs of: • 1 pc(s). EAN: • 1 pc(s).		
 Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm Surface finish: powder-coated Colour: Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey) Protection category IP to IEC 60 529: IP 55 Supply includes: Wall section Hinged part with 25 mm pitch pattern of holes in the front and rear frame Designer glazed door Wall section: Mounting plate supplied loose Hinged part with two 482.6 mm (19") mounting angles Mini-comfort handle Security lock 3524 E Packs of: 1 pc(s). 	Description:	• Wall-mounted enclosure with optimum accessibility thanks to hinged part.
• powder-coated Colour: • Wall and hinged part: RAL 7035 • Glazed door: RAL 7035/7015 (slate grey) Protection category IP to IEC 60 529: • IP 55 Supply includes: • Wall section • Hinged part with 25 mm pitch pattern of holes in the front and rear frame • Designer glazed door • Wall section: Gland plate, solid, top and bottom • Wall section: Gland plate, solid, top and bottom • Wall section: Gland plate supplied loose • Hinged part with two 482.6 mm (19") mounting angles • Mini-comfort handle • Security lock 3524 E Packs of: • 1 pc(s).	Material:	
 Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey) Protection category IP 55 Supply includes: Wall section Hinged part with 25 mm pitch pattern of holes in the front and rear frame Designer glazed door Wall section: Gland plate, solid, top and bottom Wall section: Mounting plate supplied loose Hinged part with two 482.6 mm (19") mounting angles Mini-comfort handle Security lock 3524 E Packs of: 1 pc(s). 	Surface finish:	 powder-coated
IP to IEC 60 529: • IP 55 Supply includes: • Wall section • Hinged part with 25 mm pitch pattern of holes in the front and rear frame • Designer glazed door • Wall section: Gland plate, solid, top and bottom • Wall section: Mounting plate supplied loose • Hinged part with two 482.6 mm (19") mounting angles • Mini-comfort handle • Security lock 3524 E Packs of: • 1 pc(s).	Colour:	
 Wall section Hinged part with 25 mm pitch pattern of holes in the front and rear frame Designer glazed door Wall section: Gland plate, solid, top and bottom Wall section: Mounting plate supplied loose Hinged part with two 482.6 mm (19") mounting angles Mini-comfort handle Security lock 3524 E Packs of: 1 pc(s). 		• IP 55
• 1 pc(s). EAN:	Supply includes:	 Hinged part with 25 mm pitch pattern of holes in the front and rear frame Designer glazed door Wall section: Gland plate, solid, top and bottom Wall section: Mounting plate supplied loose Hinged part with two 482.6 mm (19") mounting angles Mini-comfort handle
	Packs of:	• 1 pc(s).
• 4028177324329	EAN:	• 4028177324329

Product features	
Design:	 with mounting plate and mounting angles, static installation
Dimensions:	 Width: 600 mm Height: 478 mm Depth: 373 mm
Depth hinged part:	• 216 mm
Installation depth:	• 320 mm
Clearances:	 Clearance width: 502 mm Clearance height: 415 mm
Mounting plate:	 Width: 485 mm Height: 432 mm
Wall section:	Depth: 135 mm
Load capacity:	 Hinged part, static (max.): 45 kg
Weight:	• 33.8 kg
Approvals	
Approvals:	 ■ <u>Lloyds Register of Shipping (EN)</u> ■ <u>UL + C-UL (EN)</u> ■ <u>Germanischer Lloyd (EN)</u>
Downloads	
Data sheets:	 [™] Technical details (EN)
Documentation:	• 🔁 Instructions (EN, DE)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postfach 1662 · D-35726 Herborn Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319 E-Mail: info@rittal.com · www.rittal.com



POWER DISTRIBUTION 💙 CLIMATE CONTROL



SOFTWARE & SERVICES

IT INFRASTRUCTURE

FRIEDHELM LOH GROUP