Rittal – The System.

Faster – better – everywhere.

Wall-mounted enclosures EL, 3-part with mounting plate and mounting angles, static installation – EL 2259.605

Date : Mar 18, 2014

RITTAL

Product description

Description:	• Wall-mounted enclosure with optimum accessibility thanks to hinged part.
Material:	• Wall and hinged part: Sheet steel, 1.5 mm • Viewing window: Single-pane safety glass, 3 mm
Surface finish:	• powder-coated
Colour:	• Wall and hinged part: RAL 7035 • Glazed door: RAL 7035/7015 (slate grey)
Protection category IP to IEC 60 529:	• IP 55
Supply includes:	• Wall section • Hinged part with 25 mm pitch pattern of holes in the front and rear frame • Designer glazed door • Wall section: Gland plate, solid, top and bottom • Wall section: Mounting plate supplied loose • Hinged part with two 482.6 mm (19") mounting angles • Mini-comfort handle • Security lock 3524 E
Packs of:	• 1 pc(s).
EAN:	• 4028177324398

Customs tariff number:	• 94032080

Product features

Design:	• with mounting plate and mounting angles, static installation

Dimensions:	• Width: 600 mm • Height: 478 mm • Depth: 473 mm

Depth hinged part:	• 316 mm

Installation depth:	• 420 mm

Clearances:	• Clearance width: 502 mm • Clearance height: 415 mm

Mounting plate:	• Width: 485 mm • Height: 432 mm

Wall section:	• Depth: 135 mm

Load capacity:	• Hinged part, static (max.): 45 kg

Weight:	• 36.6 kg

Approvals

Approvals:	• Lloyds Register of Shipping (EN) • UL + C-UL (EN) • Germanischer Lloyd (EN)

Downloads

Data sheets:	• Technical details (EN)

Documentation:	• Instructions (EN, DE)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

ENCLOSURES   POWER DISTRIBUTION   CLIMATE CONTROL   IT INFRASTRUCTURE   SOFTWARE & SERVICES

RITTAL

FRIEDHELM LOH GROUP