## Rittal - The System.

Faster – better – everywhere.

# System window – FT 2736.540

Date : Mar 17, 2014



ENCLOSURES >> POWER DISTRIBUTION >> CLIMATE CONTROL >> IT INFRASTRUCTURE >> SOFTWARE & SERVICES >>

## System window - FT 2736.540

created: 17.03.2014 on www.rittal.com/com-en



## **Product description**

## Description:

 To conceal display and operating instruments or cut-outs, and to protect against dirt and liquids as well as unauthorised access.

#### Benefits:

- Base frame: Easily screw-fastened to the door thanks to modified dimensions (tubular door frame may be used as a drilling template).
- Readily height-adjustable.
- Stabilises the door cut-out.
- Conceals the cut edge.
- The rain canopy prevents dirt from landing on the seal, protects the glass from being lifted out, prevents the ingress of dirt and moisture when opening the window.
- Frame section height 30 mm or 60 mm
- Viewing window: Made from single-pane safety glass: High level of resistance to solvents and scratches, anti-static, reduced risk of injury if broken.
- Cam lock with double-bit insert, easily exchanged for lock inserts, type A, and semi-cylinders in the Ergoform-S lock system (not with 2735.500 and .560)
- Hinge with 180° opening angle, easily inserted.

#### Material:

• Extruded aluminium section with die-cast zinc corner pieces and single-pane safety glass.

#### Surface finish:

- Base frame: Powder coated on the outside in RAL 7035,
- Hinge and lock section: Natural-anodised

## Protection category IP to IEC 60 529:

• IP 54

## Packs of:

• 1 pc(s).

## EAN:

• 4028177476448

© Rittal 2013

Customs tariff number:

• 76101000

## **Product features**

Design:

• 60 section

To fit:

• Enclosure type: TS

• SE

• Width: 600 mm

**Dimensions:** 

Width: 500 mmHeight: 670 mmDepth: 77 mm

Viewing area:

Width: 365 mmHeight: 600 mm

Build depth for components (max.):

• 63 mm

## **Downloads**

**Documentation:** 

• 🔁 Instructions (EN, DE)

## Rittal – The System.

## Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postfach 1662 · D-35726 Herborn Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

> IT INFRASTRUCTURE

SOFTWARE & SERVICES



>> CLIMATE CONTROL