Rittal - The System.

Faster – better – everywhere.

■ Utility lectern for TS, SE, CM, PC – TS 4638.800

Date: Mar 17, 2014



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Utility lectern for TS, SE, CM, PC - TS 4638.800

created: 17.03.2014 on www.rittal.com/com-en



Product description

Description:

• For programming units etc. Prepared for mounting on the tubular door frame of TS, CM, ES, PC or on any sufficiently large surface. When required for servicing, it folds down quickly with a maximum support area, and after use is stowed between the tubular door frames in a space-saving design. Load capacity: max. 30 kg.

Material:

• Sheet steel

Colour:

• RAL 7035

Packs of:

• 1 pc(s).

EAN:

• 4028177107519

Customs tariff

number:

• 73269098

Product features

To fit:

- Enclosure type: TS 8
- SE 8
- CM
- PC

To fit door width:

• 800 mm

Support area:

© Rittal 2013

. .

Width: 613 mmDepth: 400 mm

Support area:

Width: 613 mmDepth: 400 mm

Load capacity:

• 30 kg

© Rittal 2013

2

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG Postfach 1662 · D-35726 Herborn Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319

E-Mail: info@rittal.com · www.rittal.com

> IT INFRASTRUCTURE

SOFTWARE & SERVICES



>> CLIMATE CONTROL