

Rittal – The System.

Faster – better – everywhere.

Standard light – SZ 4138.280

Date : Mar 17, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Standard light – SZ 4138.280

created : 17.03.2014 on www.rittal.com/com-en



Product description

Supply includes:

- Standard light
- Light
- Assembly parts

Packs of:

- 1 pc(s).

EAN:

- 4028177581418

Customs tariff number:

- 94054095

Product features

Dimensions:

- Width: 682 mm
- Height: 117 mm
- Depth: 50 mm

Rated operating voltage:

- 120 V, 1~, 60 Hz

Power consumption:

- 18 W

Equipment (electrical):

- Ballast: Magnetic ballast
- Light: Fluorescent lamp, base G13
- Protection category: I (protectively earthed)
- Connection options: Door-operated switch
- Power supply via connectors
- Through-wiring (creating rows of lights)

- Jack/socket (type): USĀ/CDN (type B, NEMA 5-15)
- Switch (type): Integral, on/off/door-operated switch mode

Light – installation type:



- Screw-fastening

Light – mounting option:

- TS vertical section, with adaptor bracket
- AE/CM/TP, with universal bracket
- AE, with rail for interior installation
- TS roof frame (horizontal section), direct


Approvals

Approvals:

-  [UR \(EN\)](#)
-  [C-UR \(EN\)](#)

Downloads

Documentation:

-  [Instructions \(SE, DE, ES, EN, FR, NL, IT\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP