

Rittal – The System.

Faster – better – everywhere.

Standard light – SZ 4138.350

Date : Mar 17, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Standard light – SZ 4138.350

created : 17.03.2014 on www.rittal.com/com-en



Product description

Supply includes:

- Standard light
- Light
- Assembly parts
- Integral door-operated switch

Packs of:

- 1 pc(s).

EAN:

- 4028177320734

Customs tariff number:

- 94054095

Product features

Dimensions:

- Width: 987 mm
- Height: 117 mm
- Depth: 50 mm

Rated operating voltage:

- 230 V, 1~, 50 Hz

Power consumption:

- 30 W

Equipment (electrical):

- Ballast: Magnetic ballast
- Light: Fluorescent lamp, base G13
- Protection category: I (protectively earthed)
- Connection options: Door-operated switch
- Power supply via connectors

- Through-wiring (creating rows of lights)
- Jack/socket (type): D, earthing-pin (type F, CEE 7/4)
- Integral door-operated switch: yes
- Switch (type): Integral, on/off/door-operated switch mode

Light – installation type:

- Screw-fastening

Light – mounting option:


- TS vertical section, with adaptor bracket
- AE/CM/TP, with universal bracket
- AE, with rail for interior installation
- TS roof frame (horizontal section), direct

Approvals

Approvals:

-  [Produktion TÜV-Geprüfte Sicherheit \(EN, DE\)](#)
-  [TÜV \(EN, DE\)](#)

Declarations:

-  [Declaration of conformity \(EN, DE\)](#)

Downloads

Documentation:

-  [Instructions \(FR, EN, DE\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP