

Rittal – The System.

Faster – better – everywhere.

Compact light – SZ 4140.020

Date : Mar 17, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Compact light – SZ 4140.020

created : 17.03.2014 on www.rittal.com/com-en



Product description

Description:

- Slimmer: Around 50% less height and depth and also around 75% less volume than conventional lights. Faster: Universal fast attachment via clips, screws, or powerful magnets (optional). Simply slide in at the side or rear, fit the light, and it's done! Brighter: Up to 75% greater luminous efficiency from the lamp with the same power helps to cut electricity costs. Door-operated switch can also be connected via a 2-pole connection.

Colour:

- Similar to RAL 7035

Protection category IP to IEC 60 529:

- IP 20

Supply includes:

- Compact light with clip and screw mounting kits
- Light
- Light cover
- Connection cable
- Assembly parts

Packs of:

- 1 pc(s).

EAN:

- 4028177522749

Customs tariff number:

- 94054095

Product features

Dimensions:

- Width: 705 mm
- Height: 59 mm

- Depth: 24 mm

Rated operating voltage:

- 100 V - 240 V, 1~, 60 Hz/
- Voltage tolerance: 10 %

Mounting dimensions:

- Mounting distance – clip/magnet: 650 mm
- Mounting distance – screw attachment: 725 mm

Rated current:

- At 230 V/50 Hz: 0.073 A - 0.127 A
- At 110 V/60 Hz: 0.149 A - 0.216 A

Power consumption:

- 14 W

Equipment (electrical):

- Ballast: Wide-range electronic ballast
- Light: Fluorescent lamp T5
- Protection category: II (all-insulated)
- Connection options: Integral connection cable with open end
- Door-operated switch
- Length of connection cable: 3 m
- Colour of cable: Yellow
- Switch (type): Integral, on/off/door-operated switch mode

Light – installation type:

- Clip attachment
- Magnetic attachment (accessory)
- Screw-fastening

Light – mounting option:

- TS roof frame (horizontal section), direct
- TS vertical section, direct
- AE/CM/TP, with magnetic attachment


Cable deflector across rear possible:

- yes

Light cover:

- yes

Approvals**Declarations:**

-  [Declaration of conformity \(EN, DE\)](#)

Downloads**Documentation:**

-  [Instructions \(SE, DE, EN, FR, NL, IT, JP\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP