

Rittal – The System.

Faster – better – everywhere.

▶ TS punched section with mounting flange, 17 x 73 mm – TS 8612.040

Date : Mar 17, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS punched section with mounting flange, 17 x 73 mm – TS 8612.040

created : 17.03.2014 on www.rittal.com/com-en



Product description

Description:

- Variable, with 5 rows of holes for universal skeleton structures or partial assembly. Simply locate into the TS punchings and secure.

Material:

- Sheet steel

Surface finish:

- zinc-plated

Supply includes:

- Assembly screws

Packs of:

- 4 pc(s).

EAN:

- 4028177212077

Customs tariff number:

- 73269098

Product features

Design:

- For the inner mounting level and for mounting on doors

To fit:

- Enclosure type: TS
- SE
- CM
- TP
- Width: 400 mm

- Depth: 400 mm

Installation options:

- On the vertical TS enclosure section: On the outer mounting level, all-round, at the same height On the inner mounting level, all-round, height-offset
- In the tubular door frame for TS, SE and PC
- For SE, may additionally be mounted on the top horizontal section in the depth
- In CM and TP via rail for interior installation: In the depth, for outer mounting level. In the width, for inner mounting level.

Length:

- 390 mm

To fit door width:

- 500 mm

Downloads**Data sheets:**

-  [Technical details \(EN\)](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

