

# Rittal – The System.

Faster – better – everywhere.

## ► TopTherm fan-and-filter units – SK 3238.110

Date : Mar 18, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TopTherm fan-and-filter units – SK 3238.110

created : 18.03.2014 on www.rittal.com/com-en



## Product description

### Colour:

- RAL 7035

### Protection category IP to IEC 60 529:

- IP 54
- With hose-proof hood: IP 56
- With fine filter mat or hose-proof hood: IP 54

### Supply includes:

- Complete unit ready to install, including filter mat

### Note:

- For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

### Packs of:

- 1 pc(s).

### EAN:

- 4028177651715

### Customs tariff number:

- 84145100

## Product features

### Air throughput (unimpeded air flow):

- At 50 Hz: 55 m<sup>3</sup>/h
- At 60 Hz: 66 m<sup>3</sup>/h






### Air throughput with outlet filter including

- Number of outlet filters: 1


<b>standard filter mat:</b>	<ul style="list-style-type: none"> <li>• 2</li> <li>• Model No. of outlet filter: SK 3238.200</li> <li>• SK 3238.200</li> <li>• At 50 Hz: 43 m<sup>3</sup>/h</li> <li>• 48 m<sup>3</sup>/h</li> <li>• At 60 Hz: 50 m<sup>3</sup>/h</li> <li>• 57 m<sup>3</sup>/h</li> </ul>
<b>Rated operating voltage:</b>	<ul style="list-style-type: none"> <li>• 115 V, 1~, 50 Hz/60 Hz</li> </ul>
<b>Dimensions:</b>	<ul style="list-style-type: none"> <li>• Width: 148.5 mm</li> <li>• Height: 148.5 mm</li> </ul>
<b>Required mounting cut-out:</b>	<ul style="list-style-type: none"> <li>• Width: 124 mm</li> <li>• Height: 124 mm</li> </ul>
<b>Build depth:</b>	<ul style="list-style-type: none"> <li>• 16 mm</li> </ul>
<b>Installation depth:</b>	<ul style="list-style-type: none"> <li>• 58.5 mm</li> </ul>
<b>Temperature range:</b>	<ul style="list-style-type: none"> <li>• Bearing: -30°C...+70°C</li> <li>• Operation (environment): -15°C...+55°C</li> </ul>
<b>Power consumption Pel:</b>	<ul style="list-style-type: none"> <li>• At 50 Hz: 19 W</li> <li>• At 60 Hz: 18 W</li> </ul>
<b>Rated current (max.):</b>	<ul style="list-style-type: none"> <li>• At 50 Hz: 0.24 A</li> <li>• At 60 Hz: 0.22 A</li> </ul>
<b>Pre-fuse:</b>	<ul style="list-style-type: none"> <li>• Miniature circuit-breaker/fuse: 2 A</li> </ul>
<b>Noise level:</b>	<ul style="list-style-type: none"> <li>• At 50 Hz: 46 dB(A)</li> <li>• At 60 Hz: 49 dB(A)</li> </ul>
<b>Diagonal fan:</b>	<ul style="list-style-type: none"> <li>• Diagonal, self-starting shaded pole motor</li> </ul>

## Approvals

### Approvals:




-  [UR + C-UR \(EN\)](#)
-  [CSA \(EN\)](#)
-  [UR \(EN\)](#)
-  [C-UR \(EN\)](#)
-  [Approval overview \(EN\)](#)

#### Declarations:









-  [Declaration of conformity \(EN, DE\)](#)

## Downloads

#### Data sheets:

-  [Technical details \(EN\)](#)
-  [Technical system catalogue \(DE\)](#)
-  [Performance diagrams \(DE\)](#)

#### Documentation:

-  [Instructions \(EN\)](#)
-  [Instructions \(DE\)](#)
-  [Instructions \(ES\)](#)
-  [Instructions \(FR\)](#)
-  [Instructions \(IT\)](#)
-  [Instructions \(JP\)](#)
-  [Instructions \(NL\)](#)
-  [Instructions \(SE\)](#)

#### CAD drawings:

- Request

Please note that there are the following alternative products:



TopTherm fan-and-filter units EMC

# Rittal – The System.

---

**Faster – better – everywhere.**

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG  
Postfach 1662 · D-35726 Herborn  
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319  
E-Mail: [info@rittal.com](mailto:info@rittal.com) · [www.rittal.com](http://www.rittal.com)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP