

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units EMC – SK 3237.600

Date : Mar 18, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units EMC – SK 3237.600

created : 18.03.2014 on www.rittal.com/com-en



Product description

Colour:

- RAL 7035

Protection category IP to IEC 60 529:

- IP 54
- With hose-proof hood: IP 56

Supply includes:

- Complete unit ready to install, including filter mat

Note:

- For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

Packs of:

- 1 pc(s).

EAN:

- 4028177652415

Customs tariff number:

- 84145100

Product features

Air throughput (unimpeded air flow):

- At 50 Hz: 20 m³/h
- At 60 Hz: 25 m³/h

Air throughput with outlet filter including standard filter mat:

- Number of outlet filters: 1
- Model No. of outlet filter: SK 3237.060

- At 50 Hz: 15 m³/h
- At 60 Hz: 18 m³/h

Rated operating voltage:

- 230 V, 1~, 50 Hz/60 Hz

Dimensions:

- Width: 116.5 mm
- Height: 116.5 mm

Required mounting cut-out:

- Width: 92 mm
- Height: 92 mm

Build depth:

- 16 mm

Installation depth:

- 43 mm

Temperature range:

- Bearing: -30°C...+70°C
- Operation (environment): -15°C...+55°C

EMC version:

- yes

**Power consumption
Pel:**

- At 50 Hz: 11 W
- At 60 Hz: 9 W

Rated current (max.):

- At 50 Hz: 0.06 A
- At 60 Hz: 0.05 A

Pre-fuse:

- Miniature circuit-breaker/fuse: 2 A

Noise level:






- At 50 Hz: 38 dB(A)
- At 60 Hz: 43 dB(A)

Diagonal fan:


- Axial, self-starting shaded pole motor

Approvals

Approvals:




-  [UR + C-UR \(EN\)](#)
-  [CSA \(EN\)](#)
-  [UR \(EN\)](#)
-  [C-UR \(EN\)](#)
-  [Approval overview \(EN\)](#)

Declarations:









-  [Declaration of conformity \(EN, DE\)](#)

Downloads

Data sheets:

-  [Technical details \(EN\)](#)
-  [Technical system catalogue \(DE\)](#)
-  [Performance diagrams \(DE\)](#)

Documentation:

-  [Instructions \(EN\)](#)
-  [Instructions \(DE\)](#)
-  [Instructions \(ES\)](#)
-  [Instructions \(FR\)](#)
-  [Instructions \(IT\)](#)
-  [Instructions \(JP\)](#)
-  [Instructions \(NL\)](#)
-  [Instructions \(SE\)](#)

CAD drawings:

- Request

Please note that there are the following alternative products:



TopTherm fan-and-filter units

Further information on this product

» www.rittal.com/com-en/TopTherm_fan_and_filter_units



[TopTherm fan-and-filter units](#)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP