

Rittal – The System.

Faster – better – everywhere.

► TopTherm air/air heat exchanger Wall-mounted with controller – SK 3126.100

Date : Mar 17, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm air/air heat exchanger Wall-mounted with controller – SK 3126.100

created : 17.03.2014 on www.rittal.com/com-en



Product description

Colour:

- RAL 7035

Protection category IP to IEC 60 529:

- Internal circuit IP 54

Supply includes:

- Complete unit ready for connection
- Plug-in terminal strip
- Floating fault signal contact in case of overtemperature

Packs of:

- 1 pc(s).

EAN:

- 4028177388956

Customs tariff number:

- 84195000

Product features

Specific thermal output:






- 17.5 W/K

Air throughput (unimpeded air flow):

- External circuit with 50 Hz: 265 m³/h
- External circuit with 60 Hz: 315 m³/h
- Internal circuit at 50 Hz: 265 m³/h
- Internal circuit at 60 Hz: 315 m³/h

Rated operating voltage:

- 230 V, 1~, 50 Hz/60 Hz

Dimensions:	<ul style="list-style-type: none"> • Width: 280 mm • Height: 550 mm • Depth: 150 mm
Temperature control:	<ul style="list-style-type: none"> • Electronic control with digital display (factory setting +35°C)
Temperature range:	<ul style="list-style-type: none"> • Operation (environment): -5°C...+55°C
Output per fan:	<ul style="list-style-type: none"> • At 50 Hz: 23 W • At 60 Hz: 27 W
Rated current (max.):	<ul style="list-style-type: none"> • per fan at 50 Hz: 0.11 A • per fan at 60 Hz: 0.13 A
Pre-fuse:	<ul style="list-style-type: none"> • Miniature circuit-breaker/fuse: 2 A
Weight:	<ul style="list-style-type: none"> • 10 kg
Approvals	
Approvals:	<ul style="list-style-type: none"> •  C-UR (EN) •  Approval overview (EN) •  C-UR (EN)
Declarations:	<ul style="list-style-type: none"> •  Declaration of conformity (EN, DE)
Downloads	
Documentation:	<ul style="list-style-type: none"> •  Instructions (SE, DE, ES, EN, FR, NL, IT)
CAD drawings:	<ul style="list-style-type: none"> • Request

Please note that there are the following alternative products:



Air/air heat exchangers Roof-mounted



Air/air heat exchangers, wall-mounted without control



Air/air heat exchangers, wall-mounted Railway-compatible version

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP