

# SSRPCDS75A2

solid state relay - panel mounting - input 3-32 V DC, output 48-530 V AC, 75A



## Main

Commercial Status	Commercialised
Range of product	Zelio Relay
Product or component type	Solid state relay
Device short name	SSR
Mounting support	Panel
[In] rated current	75 A
Output voltage	48...530 V AC
[Uc] control circuit voltage	4...32 V
Control circuit type	DC

## Complementary

Contacts type and composition	1 NO
Tightening torque	<= 2.2 N.m for output <= 1.1 N.m for input
Local signalling	LED green for input status
Switching voltage	1 V DC turn-off 4 V DC turn-on
Input current limits	10 mA
Solid state output type	Zero voltage switching SCR output
Load current	0.15...75 A
Output sustained overvoltage	1200 V
Surge current	1000 A for 16.6 ms
Voltage drop	1.6 V on-state
Thermal resistance	0.31 °C/W
Maximum I <sup>2</sup> t for fusing	4150 A <sup>2</sup> .s for 8.3 ms
Leakage current	<= 1 mA off-state
DV/Dt	500 V/μs off-state at maximum voltage
Response time	0.5 cycle turn-off 0.5 cycle turn-on

## Environment

Standards	UL E258297 CSA LR 40487 IEC 60950-1 IEC 62314
Marking	CE
IP degree of protection	IP20
Ambient air temperature for operation	-40...80 °C
Ambient air temperature for storage	-40...125 °C

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.