

Main

Range of product	Modicon STB distributed I/O solution
Product or component type	Standard analog input kit
Kit composition	STBART0200 module STBXBA1000 base STBXTS1100, 6-terminal screw type connector STBXTS2100, 6-terminal spring clamp connector
Analogue input type	Voltage +/- 80 mV Temperature probe -100...+260 °C Cu 10 2, 3 or 4 wires IEC Temperature probe -100...+450 °C Pt 100 2, 3 or 4 wires US/JIS Temperature probe -100...+450 °C Pt 1000 2, 3 or 4 wires US/JIS Temperature probe -200...+850 °C Pt 100 2, 3 or 4 wires IEC Temperature probe -200...+850 °C Pt 1000 2, 3 or 4 wires IEC Temperature probe -60...+180 °C Ni 100 2, 3 or 4 wires IEC Temperature probe -60...+180 °C Ni 1000 2, 3 or 4 wires IEC Thermocouple +130...+1820 °C thermocouple B Thermocouple -200...+760 °C thermocouple J Thermocouple -270...+1000 °C thermocouple E Thermocouple -270...+1370 °C thermocouple K Thermocouple -270...+400 °C thermocouple T Thermocouple -50...+1665 °C thermocouple R Thermocouple -50...+1665 °C thermocouple S
Analogue input number	2
Analogue input resolution	15 bits + sign
Type of filter	Single low pass input filter 25 Hz

Complementary

Absolute maximum input	+/- 7.5 V DC
Cold swapping	Yes
Hot swapping fallback	Yes for standard NIMs
Fallback status	State 0 basic NIMs User configurable standard NIMs
Data format	EN 61131-2 IEC 61131-2
Input impedance	10 MOhm +/- 80 mV
Supply current for sensors	100 mA per input channels
Protection type	Short-circuit protection
Absolute accuracy error	+/- 0.1 % of full scale 25 °C internal +/- 0.15 % of full scale 25 °C external
Insulation between channels and logic bus	1500 V for 1 minute
Addressing requirement	1 word for cold-junction compensation 2 input words
Product compatibility	Mounting base STBXBA1000 Power distribution module STBPDT3100/3105
[Us] rated supply voltage	24 V DC
Supply	Power distribution module
Current consumption	30 mA 5 V DC logic bus
Measurement resolution	0.01 mV voltage 0.1 °C or 0.1 °F temperature probe 0.1 °C or 0.1 °F thermocouple
Conversion time	150 ms voltage 60 Hz 170 ms voltage 50 Hz 180 ms temperature probe 60 Hz 2 or 4 wires 200 ms temperature probe 50 Hz 2 or 4 wires 210 ms thermocouple with internal cold-junction compensation 60 Hz 230 ms thermocouple with internal cold-junction compensation 50 Hz 300 ms temperature probe 60 Hz 3 wires 340 ms temperature probe 50 Hz 3 wires 360 ms thermocouple with external cold-junction compensation 60 Hz

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Maximum wiring resistance	20 Ohm Cu 10 IEC/US/JIS 2 or 3 wires 20 Ohm Ni 100 IEC/US/JIS 2 or 3 wires 20 Ohm Pt 100 IEC/US/JIS 2 or 3 wires 200 Ohm Ni 1000 IEC/US/JIS 2 or 3 wires 200 Ohm Pt 1000 IEC/US/JIS 2 or 3 wires 50 Ohm Cu 10 IEC/US/JIS 4 wires 50 Ohm Ni 100 IEC/US/JIS 4 wires 50 Ohm Pt 100 IEC/US/JIS 4 wires 500 Ohm Ni 1000 IEC/US/JIS 4 wires 500 Ohm Pt 1000 IEC/US/JIS 4 wires
Measurement accuracy	+/- 1 °C Ni 100 25 °C external +/- 1 °C Ni 100 25 °C internal +/- 1 °C Ni 1000 25 °C external +/- 1 °C Ni 1000 25 °C internal +/- 1 °C Pt 100 25 °C internal +/- 1 °C Pt 1000 25 °C internal +/- 1.75 °C thermocouple B with external cold-junction compensation 25 °C +/- 1.75 °C thermocouple E with external cold-junction compensation 25 °C +/- 1.75 °C thermocouple J with external cold-junction compensation 25 °C +/- 1.75 °C thermocouple K with external cold-junction compensation 25 °C +/- 1.75 °C thermocouple R with external cold-junction compensation 25 °C +/- 1.75 °C thermocouple S with external cold-junction compensation 25 °C +/- 1.75 °C thermocouple T with external cold-junction compensation 25 °C +/- 2 °C Pt 100 25 °C external +/- 2 °C Pt 1000 25 °C external +/- 2.85 °C thermocouple B with external cold-junction compensation 60 °C +/- 2.85 °C thermocouple E with external cold-junction compensation 60 °C +/- 2.85 °C thermocouple J with external cold-junction compensation 60 °C +/- 2.85 °C thermocouple K with external cold-junction compensation 60 °C +/- 2.85 °C thermocouple R with external cold-junction compensation 60 °C +/- 2.85 °C thermocouple S with external cold-junction compensation 60 °C +/- 2.85 °C thermocouple T with external cold-junction compensation 60 °C +/- 3.6 °C thermocouple R with internal cold-junction compensation 25 °C +/- 4 °C Cu 10 25 °C external +/- 4 °C Cu 10 25 °C internal +/- 4 °C thermocouple K with internal cold-junction compensation 25 °C +/- 4.1 °C thermocouple S with internal cold-junction compensation 25 °C +/- 4.2 °C thermocouple R with internal cold-junction compensation 60 °C +/- 4.4 °C thermocouple T with internal cold-junction compensation 25 °C +/- 4.6 °C thermocouple B with internal cold-junction compensation 25 °C +/- 4.6 °C thermocouple E with internal cold-junction compensation 25 °C +/- 5 °C thermocouple S with internal cold-junction compensation 60 °C +/- 5.1 °C thermocouple J with internal cold-junction compensation 25 °C +/- 5.5 °C thermocouple K with internal cold-junction compensation 60 °C +/- 6.4 °C thermocouple T with internal cold-junction compensation 60 °C +/- 6.8 °C thermocouple B with internal cold-junction compensation 60 °C +/- 6.8 °C thermocouple E with internal cold-junction compensation 60 °C +/- 7 °C thermocouple J with internal cold-junction compensation 60 °C
Marking	CE
Overvoltage category	II
Status LED	1 LED green module status (RDY) 1 LED red module error (ERR)

Environment

Product certifications	ATEX Cat 3G CSA C-Tick FM Class 1 Division 2 UL
Pollution degree	2 IEC 60664-1
Operating altitude	<= 2000 m
IP degree of protection	IP20 EN 61131-2 class 1
Ambient air temperature for operation	0...70 °C
Ambient air temperature for operation	32...140 °F without
Ambient air temperature for storage	-40...85 °C without
Ambient air temperature for storage	-40...185 °F without
Relative humidity	95 % 60 °C without condensation
Vibration resistance	+/-0.35 mm 10...58 Hz 3 gn 58...150 Hz 35 x 7.5 mm symmetrical DIN rail 5 gn 58...150 Hz 35 x 15 mm symmetrical DIN rail

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0825 - Schneider Electric declaration of conformity
Product environmental profile	Available

Contractual warranty

Period	18 months
--------	-----------
