



Main

Range of product	Modicon STB distributed I/O solution
Product or component type	Standard power distribution kit

Complementary

Kit composition	STBPDT2100 module STBXBA2200 base STBXTS1130, screw type connectors STBXTS2130, spring type connectors
[Us] rated supply voltage	115...230 V
Supply circuit type	AC
Supply frequency	50...60 Hz
Power supply output current	0...10 A 30 °C output circuit 0...2.5 A 60 °C input circuit 0...5 A 30 °C input circuit 0...5 A 60 °C output circuit
Voltage range	85...265 V AC sensor/actuator bus
Hot swapping fallback	Hot swapping illegal
Protection type	Built-in overcurrent protection 10 A time-lag output circuit Built-in overcurrent protection 5 A time-lag input circuit
Permissible current	0...30 A for 2 minutes grounding terminal
Voltage detection threshold	< 50 V +/-5 AC IN/OUT LED non lit > 70 V +/-5 AC IN/OUT LED lit
Product compatibility	Mounting base STBXBA2200
Marking	CE
Overvoltage category	II
Status LED	1 LED green actuator bus power supply (OUT) 1 LED green sensor bus power supply (IN)
Depth	65.1 mm
Height	18.4 mm
Width	125 mm
Product weight	0.129 kg

Environment

Product certifications	CSA FM Class 1 Division 2 UL
Pollution degree	2 IEC 60664-1
Operating altitude	<= 2000 m
IP degree of protection	IP20 EN 61131-2 class 1
Ambient air temperature for operation	0...60 °C without derating
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % 60 °C without condensation
Vibration resistance	+/-0.35 mm 10...58 Hz 3 gn 58...150 Hz 35 x 7.5 mm symmetrical DIN rail 5 gn 58...150 Hz 35 x 15 mm symmetrical DIN rail

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Shock resistance

30 gn 11 ms IEC 88 reference 2-27

Offer Sustainability

Sustainable offer status

Not Green Premium product

RoHS

Compliant - since 0952 - Schneider Electric declaration of conformity

Contractual warranty

Period

18 months
