

### Main

Commercial Status	Commercialised
Product or component type	DC choke
Range compatibility	Altivar 61 Altivar 71
Product specific application	Reduction of current harmonics
Value of inductance	3.9 mH
[In] rated current	10.7 A
Thermal losses	27 W
Product compatibility	ATV61HU40N4 ATV71HU40N4 ATV71PU40N4Z ATV71WU40N4
Electrical connection	Power supply terminal, connection capacity: 2.5 mm <sup>2</sup> (AWG 12) Earth circuit terminal, connection capacity: 10 mm <sup>2</sup> (AWG 6)

### Complementary

Network number of phases	3 phases
Supply frequency	50...60 Hz
Voltage drop at rated load	4...6 %
Max current	1.65 x nominal current for 60 s
Tightening torque	Power supply 0.4...0.6 N.m Earth circuit 1.2...1.4 N.m
Height	134 mm
Width	96 mm
Depth	115 mm
Product weight	1.65 kg

### Environment

IP degree of protection	IP20
Relative humidity	<= 95 %
Ambient air temperature for operation	-10...50 °C without current derating > 50...60 °C with current derating 2.2 % per °C
Ambient air temperature for storage	-40...65 °C
Operating altitude	1000...3000 m with current derating 1 % per 100 m <= 1000 m without current derating

### Contractual warranty

Period	18 months
--------	-----------