

# NSYS3D101030P

Spacial S3D plain door with mount.plate.  
H1000xW1000xD300 IP66 IK10 RAL7035.



## Main

|                             |   |
|-----------------------------|---|
| Range of product            | Spacial S3D   |
| Device application          | Multi-purpose   |
| Product or component type   | Compact enclosure   |
| Enclosure nominal height    | 1000 mm   |
| Enclosure nominal width     | 1000 mm   |
| Enclosure nominal depth     | 300 mm  |
| Door type                   | Plain   |
| Mounting plate description  | Plain   |
| Type of gland plate         | Standard  |
| Installation accessory type | Wall-mounting   |
| Device composition          | Body 1<br>Cable gland plate 2<br>Mounting plate 1<br>Door with lock 1 |

## Complementary

|                             |   |
|-----------------------------|---|
| Variant particularity       | Gutter-shaped front rail double sheet thickness<br>Single piece body              |
| Number of doors             | 1 front face  |
| Door opening                | Reversible 120 °  |
| Lock type                   | 3 points lock, 3 mm double-bar  |
| Accessibility for operation | Front   |
| Removable parts             | Door by hinges<br>Cable gland plate by screws<br>Mounting plate by fixing element |
| Material                    | Galvanised steel for mounting plate<br>Steel for enclosure                        |
| Surface finish              | Epoxy-polyester powder enclosure  |
| Colour                      | Grey RAL 7035 enclosure :   |
| Standards                   | IEC 62208   |
| Product certifications      | BV<br>CUL<br>DNV<br>GL<br>LR<br>UL  |

## Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0940 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

---

Period

18 months

---