NSYS3D6625T

Spacial S3D tspt door w/o mount.plate H600xW600xD250.IP66 IK08 RAL7035.





Main

Range of product	Spacial S3D
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	600 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	250 mm
Door type	Glazed
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	Lock 1 Door 1 Body 1
	Cable gland plate 1

Complementary

Variant particularity	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	1 front face	
Door opening	Reversible 120 °	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	Steel for body Steel and security glass for door	
Surface finish	Epoxy-polyester powder	
Colour	Grey RAL 7035	
Standards	IEC 62208	
Product certifications	BV CUL DNV GL LR UL	

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0940 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty



Period 18 months

