NSYS3X4320

SPACIAL S3X stainless 304L, Scotch Brite® finish, H400xW300xD200 mm.





Main

| Range of product | Spacial S3X |
|-----------------------------|-------------------------------------|
| Device application | Multi-purpose |
| Product or component type | Compact enclosure |
| Enclosure nominal height | 400 mm |
| Enclosure nominal width | 300 mm |
| Enclosure nominal depth | 200 mm |
| Installation accessory type | Wall-mounting |
| Device composition | 1 body 1 door 1 lock (door) |

Complementary

| Body type | Single piece body, cross-shaped structure Gutter shaped front rail | |
|-----------------------------|--|--|
| Door type | Plain | |
| Number of doors | Front face: 1 door(s) | |
| Door opening | 120°, reversible | |
| Lock type | 3 mm double-bar lock | |
| Mounting plate description | Without mounting plate | |
| Type of gland plate | Without gland plate | |
| Accessibility for operation | Front | |
| Removable parts | Door fixing: by hinges | |
| Material | Body and door: stainless steel 304L Hinge: stainless steel Lock: zamak | |
| Surface finish | Lock: chromium plated Body and door: Scotch-Brite® brushed | |
| Thickness | 1.5 mm | |

Environment

| Standards | IEC 62208 | |
|------------------------------|-------------------------------|---|
| Product certifications | CAN/CSA 22 UL 508 type A | |
| IP degree of protection | IP66 conforming to IEC 60529 | |
| IK degree of protection | IK10 conforming to IEC 62262 | : |
| Environmental characteristic | Corrosive Specific hygiene | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------------|---|--|
| RoHS | Compliant - since 0940 - Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| Product environmental profile | Available | |
| Product end of life instructions | Need no specific recycling operations | |

Contractual warranty

| Period | 18 months |
|--------|-----------|

