



### Main

Range	Spacial SM
Product or component type	Compact enclosure
Application	Multi-purpose
Installation accessory type	Floor-standing
Device composition	1 mounting plate 1 door 4 mounting plate bracket 1 locking system with handle for door 1 cable gland plate 1 body
Removable parts	Mounting plate fixed by screws for mounting plate bracket Mounting plate bracket fixed by screws Door fixed by screws for hinge
Enclosure nominal height	2000 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	500 mm

### Complementary

Number of doors	1 on front
Door opening	Reversible 120 °
Door type	Plain
Lock type	4 points lock, handle with 5 mm double bar insert
Body type	Single piece body with welded rear panel Front part forming a rigid frame with welded corners
Mounting plate description	Plain
Type of gland plate	Standard
Cable entry	1 entry
Material	Zamak for hinge Sheet steel for door Sheet steel for body Galvanised steel for mounting plate
Surface finish	Epoxy-polyester powder
Colour	Handle: black RAL 9005 Enclosure: grey RAL 7035
Accessibility for operation	Front

### Environment

Standards	IEC 62208
Product certifications	BV DNV UL
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations