



Main

Commercial Status	Commercialised
Range	Spacial SBMB
Device application	Multi-purpose
Category	Industrial box
Enclosure type	Bus box
Enclosure nominal height	200 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	120 mm
Enclosure mounting	Wall mounted
Device composition	1 x DIN rail 1 x glazed door 2 x cover screw 2 x FL21 cable gland plate 1 x body
Body type	Single piece body folded and welded
Type of front cover	Glazed door
Cover fixing	Half turn metal screw
Lock type	Outside sealed area: PZ2 screwdriver captive screw
Removable parts	DIN rail, screw Cable gland plate, screw Cover, by captive screws

Complementary

Material	Sheet steel (body) Steel and plexiglass (cover)
Surface finish	Polyester powder
Colour	Grey (RAL 7035)
Standards	IEC 62208
Product certifications	BV DNV GL LR UL
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Ambient air temperature for storage	-35...60 °C
Operating temperature	-35...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1241 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations