Product data sheet Characteristics

NSYSBS503020

Steel S3D Box +Screw 500x300x200



Main

Commercial Status	Commercialised
Range of product	Spacial S3D
	Spacial CRN
Application	Terminal application
Category	Compact enclosure
Enclosure nominal height	500 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	200 mm
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory	Wall-mounting
type	Horizontal or vertical position
Product destination	For equipping with terminal
Device composition	Lock 1
	Door 1
	Body 1

Complementary

Body type	Single piece body
Number of doors	1 front face
Lock type	Screwed on
Accessibility for operation	Front
Removable parts	Cover by 4 CHc M5x35 shouldered captive screws
Material	Steel
Surface finish	Epoxy-polyester powder
Colour	Grey RAL 7035
Standards	IEC 62208
Product certifications	LACIE (BV)

Environment

IP degree of protection	IP66 conforming to IEC 60529	177
IK degree of protection	IK10 conforming to IEC 62262	9

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0940 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold