


LTMR08PFM

motor controller LTM R TeSys T - 100..240 V AC 8 A
for Profibus DP



Main

Range of product	TeSys T
Device short name	LTMR
Product or component type	Motor controller
Communication port protocol	Profibus DP
Control circuit voltage	100...240 V AC
Current range	0.4...8 A
[Ue] rated operational voltage	93.5...264 V AC
Input type	Logic input
Bus type	Profibus DP polarised 2-wire RS485 interface, addressing 1...125, transmission rate 9.6 kbit/s...12 Mbit/s, SUB-D 9 with 2 shielded twisted pairs, type A Profibus DP polarised 2-wire RS485 interface, addressing 1...125, transmission rate 9.6 kbit/s...12 Mbit/s, terminal block with 2 shielded twisted pairs, type A

Complementary

Logic input number	6
Discrete output function	1 NO + 1 NC fault signalling 3 NO
Protection type	GG fuse 4 A for output GG fuse 0.5 A for control circuit
Typical current consumption	56...127 mA, 50/60 Hz
Connection pitch	5.08 mm
Connections - terminals	Connector, 1 flexible cable with cable end 0.25...2.5 mm ² /AWG 24...14 for control circuit Connector, 1 flexible cable without cable end 0.2...2.5 mm ² /AWG 24...14 for control circuit Connector, 1 flexible cable without cable end 0.25...2.5 mm ² /AWG 24...14 for control circuit Connector, 1 solid cable without cable end 0.2...2.5 mm ² /AWG 24...14 for control circuit Connector, 2 flexible cable with cable end 0.2...1 mm ² /AWG 24...14 for control circuit Connector, 2 flexible cable without cable end 0.2...1.5 mm ² /AWG 24...14 for control circuit Connector, 2 flexible cable without cable end 0.5...1.5 mm ² /AWG 24...14 for control circuit Connector, 2 solid cable without cable end 0.2...1 mm ² /AWG 24...14 for control circuit
Tightening torque	0.5...0.6 N.m, 3 mm flat screwdriver for control circuit
[Ui] rated insulation voltage	690 V, category III (degree of pollution: 3) CSA C22.2 No 14 certified conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kV for supply, inputs and outputs conforming to EN/IEC 60947-4-1 6 kV for current or voltage measurement circuit conforming to EN/IEC 60947-4-1 0.8 kV for communication circuit conforming to EN/IEC 60947-4-1
Short-circuit withstand	100 kA conforming to EN/IEC 60947-4-1
Input current	3.1 mA at 100 V 7.5 mA at 240 V
Input voltage	0...40 V at state 0 79...264 V at state 1
Input current limits	<= 15 mA at state 0 >= 2 mA at state 1
Load current	5 A at 250 V AC for logic output 5 A at 30 V DC for logic output
Permissible power	480 VA (AC-15), I _e = 2 A, 500000 cycles (output) 30 W (DC-13), I _e = 1.25 A, 500000 cycles (output)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Maximum operating frequency	2 Hz
Operating rate	1800 cyc/h
Response time	25 ms at state 0 for logic input 25 ms at state 1 for logic input
Measurement accuracy	+/- 30 min/year internal clock 0,02 temperature 5...15 % earth fault current internal measurement (for current > 0.1 A) 1 % current 1 % voltage (100...830 V) 5 % active and reactive power 5 % earth fault current external measurement (< 5 % or 0.01 A) 3 % power factor (cos ϕ > 0.6)
Width	91 mm
Height	61 mm
Depth	122.5 mm
Product weight	0.53 kg

Environment

Immunity to voltage dips	70 % of U for 500 ms conforming to EN/IEC 61000-4-11
Standards	EN 60947-4-1 IACS E10 IEC 60947-4-1 UL 508 CSA C22.2 No 14
Product certifications	ABS ATEX BV CCC CSA C-Tick DNV GL GOST KERI LROS (Lloyds register of shipping) NOM RINA RMRoS UL
Protective treatment	12 x 24 hour cycles conforming to EN/IEC 60068-2-30 48 h conforming to EN/IEC 60070-2-11 TH conforming to EN/IEC 60068
Ambient air temperature for operation	-20...60 °C (operation) -40...80 °C (storage)
Fire resistance	650 °C conforming to EN/IEC 60695-2-12 960 °C conforming to UL 94
Shock resistance	15 gn (duration = 11 ms) for half sine wave acceleration conforming to EN/IEC 60068-2-27
Vibration resistance	1 gn (f = 5...300 Hz) mounted on symmetrical rail conforming to EN/IEC 60068-2-6 4 gn (f = 5...300 Hz) plate mounted conforming to EN/IEC 60068-2-6
Resistance to electrostatic discharge	6 kV, level 3 (on contact) conforming to EN/IEC 61000-4-2 8 kV, level 3 (in open air) conforming to EN/IEC 61000-4-2
Resistance to radiated fields	10 V/m, level 3 conforming to EN/IEC 61000-4-3
Resistance to fast transients	2 kV, level 3 (other circuits) conforming to EN/IEC 61000-4-4 4 kV, level 4 (on supply and relay outputs) conforming to EN/IEC 61000-4-4
Immunity to radioelectric fields	10 V, level 3 conforming to EN/IEC 61000-4-6
Non-dissipating shock wave	0.5 kV (serial mode) for temperature sensor conforming to EN/IEC 61000-4-5 1 kV (common mode) for temperature sensor conforming to EN/IEC 61000-4-5 1 kV (serial mode) for control circuit conforming to EN/IEC 61000-4-5 2 kV (common mode) for communication conforming to EN/IEC 61000-4-5 2 kV (common mode) for control circuit conforming to EN/IEC 61000-4-5 2 kV (serial mode) for relay outputs and supply conforming to EN/IEC 61000-4-5 4 kV (common mode) for relay outputs and supply conforming to EN/IEC 61000-4-5