

ABL8RPM24200

regulated SMPS - 1 or 2-phase - 100..240 V - 24 V - 20 A



Main

Range of product	Phaseo
Product or component type	Power supply
Power supply type	Regulated switch mode
Input voltage	100...120 V AC single phase, terminal(s): N-L1 200...240 V AC phase to phase, terminal(s): L1-L2
Output voltage	24 V DC
Rated power in W	480 W
PFC filter	With PFC filter conforming to IEC 61000-3-2
Power supply output current	20 A
Output protection type	Against overload, protection technology: manual or automatic reset Against overvoltage, protection technology: 30...32 V, manual reset Against short-circuits, protection technology: manual or automatic reset Against undervoltage, protection technology: tripping if $U < 21.6$ V Thermal, protection technology: automatic reset
Ambient air temperature for operation	

Complementary

Input voltage limits	170...264 V 85...132 V
Network frequency	47...63 Hz
Inrush current	≤ 30 A for 2 ms
Cos phi	0.68 at 240 V 0.69 at 120 V
Efficiency	88...100 %
Output voltage limits	24...28.8 V adjustable
Power dissipation in W	57.6 W
Line and load regulation	1...3 %
Residual ripple	
Holding time	≥ 120 ms at 400 V ≥ 20 ms at 100 V ≥ 40 ms at 240 V
Permissible temporary current boost	$1.5 \times I_n$ for 4 s
Connections - terminals	Removable screw terminal block for diagnostic relay, connection capacity: 2×2.5 mm ² Screw type terminals for input connection, connection capacity: $3 \times 0.5...3 \times 4$ mm ² AWG gauge22...12 Screw type terminals for input ground connection, connection capacity: $1 \times 0.5...1 \times 4$ mm ² AWG gauge22...12 Screw type terminals for output connection, connection capacity: $4 \times 0.5...4 \times 4$ mm ² AWG gauge22...12
Marking	CE
Mounting support	35 x 15 mm symmetrical DIN rail 35 x 7.5 mm symmetrical DIN rail
Operating position	Vertical
Output coupling	Parallel Series
Name of test	Conducted emissions on the power line conforming to EN 55022 Class B Electrostatic discharges conforming to EN/IEC 61000-4-2 Induced electromagnetic field conforming to EN/IEC 61000-4-6 Magnetic field conforming to EN 61000-4-8

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Primary outage conforming to IEC 61000-4-11
 Radiated electromagnetic field conforming to EN/IEC 61000-4-3
 Radiated emissions conforming to EN 55022 Class B
 Rapid transient conforming to IEC 61000-4-4
 Surge conforming to EN/IEC 61000-4-5
 Harmonic current emission conforming to EN/IEC 61000-3-2


Status LED	1 LED green and red for output voltage 1 LED green, red and orange for output current
Depth	155 mm
Height	143 mm
Width	165 mm
Product weight	1.6 kg

Environment

Product certifications	CCSAus C-Tick UL
Environmental characteristic	EMC conforming to EN 61000-6-1 EMC conforming to EN 61000-6-3 EMC conforming to EN/IEC 61000-6-2 EMC conforming to EN/IEC 61000-6-4 EMC conforming to EN/IEC 61204-3 Safety conforming to EN/IEC 60950-1 Safety conforming to EN/IEC 61204-3 Safety conforming to SELV
IP degree of protection	IP10 for output terminal conforming to EN/IEC 60529 IP20 conforming to EN/IEC 60529
Ambient air temperature for storage	-40...70 °C
Relative humidity	0...90 % during operation 0...95 % in storage
Class of protection against electric shock	Class I conforming to VDE 0106-1
Dielectric strength	2500 V between input and ground 3000 V between input and output 500 V between output and ground

Regulated Switch Mode Power Supply


Internal Wiring Diagram




Regulated Switch Mode Power Supply

Line Supply Wiring Diagram


Single-phase (L-N) 100 to 120 V



Phase-to-phase (L1-L2) 200 to 500 V



Single-phase (L-N) 200 to 500 V




Regulated Switch Mode Power Supplies

Derating

The ambient temperature is a determining factor that limits the power an electronic power supply can deliver continuously. If the temperature around the electronic components is too high, their life will be significantly reduced.

The nominal ambient temperature for the Universal range of Phaseo power supplies is 50°C. Above this temperature, derating is necessary up to a maximum temperature of 60°C.

The graph below shows the power (in relation to the nominal power) that the power supply can deliver continuously, depending on the ambient temperature.



X Maximum operating temperature (°C)

ABL 8RPM, ABL 8RPS, ABL 8WPS mounted vertically


Derating should be considered in extreme operating conditions:

- Intensive operation (output current permanently close to the nominal current, combined with a high ambient temperature)
- Output voltage set above 24 Vdc (to compensate for line voltage drops, for example)
- Parallel connection to increase the total power

Regulated Switch Mode Power Supply


Load Limit

Manual Reset Protection Mode




(1) Boost 4s

Automatic Reset Protection Mode



(1) Boost 4s

“Boost” Repeat Accuracy



This type of operation is described in detail in the user manual, which can be downloaded from the website.