

ABT7PDU010G

voltage transformer - 230..400 V - 2 x 115 V - 100 VA



Main

Range of product	Phaseo Universal
Product or component type	Safety and isolation transformer
Rated power in VA	100 VA
Input voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2
Output voltage	115/230 V AC
Secondary winding	Double
Protective cover	With
Ambient air temperature for operation	-20...60 °C

Complementary

Input voltage limits	207...253 V 360...440 V
Network frequency limits	47...63 Hz
Input voltage tolerance	+/- 15 V
Efficiency	86 %
Power dissipation in W	16.3 W
Voltage variation at nominal load	0,0417 at 400 V 4 % at 230 V
Output sustained overvoltage	0,049 (no load, hot state)
Voltage drop at rated load	4.23 %
No load losses	11.26 W
Short-circuit voltage	0,062
Output protection type	Against overload, protection technology: external Against overvoltage, protection technology: external Against short-circuits, protection technology: external
Connections - terminals	Screw type terminals for input connection, connection capacity: 5 x 4 mm ² AWG gauge11 Screw type terminals for input ground connection, connection capacity: 1 x 4 mm ² AWG gauge11 Screw type terminals for output connection, connection capacity: 4 x 4 mm ² AWG gauge11
Marking	CE
Fixing mode	By clips on 35 x 15 mm symmetrical DIN rail By 4 screws, screw(s) Ø = 5.5 mm on horizontal panel with derating to 90 % By 4 screws, screw(s) Ø = 5.5 mm on vertical panel, operating position: horizontal By 4 screws, screw(s) Ø = 5.5 mm on vertical panel, operating position: vertical
Output coupling	Grounding of secondary Parallel Series by internal jumper
Electrical insulation class	Class B
Status LED	1 LED orange for input voltage
Product weight	2.86 kg

Environment

Product certifications	CURus ENEC
IP degree of protection	IP20 conforming to EN/IEC 60529
Ambient air temperature for storage	-40...80 °C
Relative humidity	0...95 % during operation
Class of protection against electric shock	Class I conforming to VDE 0106-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dielectric strength

3200 V between input and ground
3200 V between output and ground
5100 V between input and output
