

Main

| | |
|---------------------------------------|---|
| Commercial Status | Commercialised |
| Range of product | Preventa Safety detection |
| Accessory / separate part category | Protection accessories |
| Accessory / separate part type | Protective cover |
| Accessory / separate part designation | Lexan protective covers for transmitter-receiver pair |
| Product compatibility | XUSLB...0600 XUSLDM...0600 |
| Accessory / separate part destination | Safety light curtain type 4 |
| Height | 630 mm |
| Quantity per set | Set of 2 |

Complementary

| | |
|--|----------|
| Material | Lexan |
| Sensing distance reduction coefficient | 0.91 Sn |
| Product weight | 0.569 kg |

Environment

| | |
|---------------------------------------|---|
| Resistance to chemical agents | Acids Aliphatic hydrocarbons Limited resistant against alcohols Limited resistant against alkalis Limited resistant against greases and oil Limited resistant against detergents and cleaners Not resistant against amines Not resistant against esters Not resistant against ketones Not resistant against aromatic hydrocarbons Not resistant against halogenated hydrocarbons Not resistant against detergents and cleaners containing alkaline products Not resistant against silicone oils and greases containing alkaline products Limited resistant against silicone oils and greases without alkaline products |
| Ambient air temperature for operation | 0...55 °C |
| Ambient air temperature for storage | -25...70 °C |

RoHS compliance

| | |
|--------------------------------|-----------|
| RoHS EUR status | Compliant |
| RoHS EUR conformity date(YYWW) | 1102 |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|