


XPSOT3444

module XPSOT - stop at top dead center with automatic overtravel - 115 V AC



Main

Range of product	Preventa Safety automation
Product or component type	Preventa safety module
Safety module name	XPSOT
Safety module application	Safety stop with automatic overtravel monitoring and control
Function of module	Safety stop with automatic overtravel monitoring and control
Safety level	Can reach PL e/category 4 conforming to EN/ISO 13849-1 Can reach SILCL 3 conforming to EN/IEC 62061
Safety reliability data	DC = 0...99 % conforming to EN/ISO 13849-1 MTTFd = 60.9 years conforming to EN/ISO 13849-1 PFHd = 1.33E-8 1/h conforming to EN/IEC 62061
[Us] rated supply voltage	115 V AC (- 15...15 %)
Output type	Relay 3 NO, volt-free
Number of additional circuits	4 solid state outputs
Enclosure type	Removable

Complementary

Supply frequency	50/60 Hz
Power consumption	< 12 VA
Input protection type	Internal, electronic
Breaking capacity	C300 : holding 180 VA AC-15 for relay output C300 : inrush 1800 VA AC-15 for relay output
Breaking capacity	1.5 A / 24 V - L/R = 50 ms, DC-13 for relay output 10 mA / 48 V for solid state output circuit 20 mA / 24 V for solid state output circuit
[Ith] conventional free air thermal current	<= 2.5 A
Associated fuse rating	4 A gG for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum output current	10 mA for relay output
Minimum output voltage	17 V for relay output
Response time on input open	<= 20 ms
[Ui] rated insulation voltage	300 V, degree of pollution 2 conforming to IEC 60647-5-1, DIN VDE 0110 part 1
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III, conforming to IEC 60647-5-1, DIN VDE 0110 part 1
Local signalling	4 LEDs
Enclosure material	Polycarbonate
Number of terminal blocks	42
Connections - terminals	Captive screw clamp terminals: 2 x 0.5...2 x 1.5 mm ² with cable end Captive screw clamp terminals: 2 x 2.5 mm ² without cable end
Mounting support	35 mm symmetrical DIN rail
Depth	118 mm
Height	73 mm
Width	200 mm
Product weight	1.1 kg

Environment

Standards	EN 60204-1 EN 692 EN/IEC 60947-5-1
Product certifications	CSA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

TÜV
UL

IP degree of protection	IP40(enclosure) conforming to EN/IEC 60529 IP10(terminals) conforming to EN/IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C

Contractual warranty

Period	18 months
--------	-----------
