


KNA63AB4

Canalis - feed unit for KNA - 63 A - left or right mounting



Main

Range of product	Canalis
Product name	KN
Product or component type	Feed unit
Material	Aluminium
Product compatibility	KN
[Ie] rated operational current	40 A 63 A
Mounting location	Side of trunking

Complementary

Protection type	Without protection
[Ue] rated operational voltage	230...500 V
Connections - terminals	Terminal block for 16 mm ² flexible Terminal block for 25 mm ² rigid
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By clips
Mounting support	Busbar
Standards	IEC 60439-2 IEC 61439-6
Width	265 mm
Depth	71 mm
Height	92 mm
Colour	White : RAL 9001
Product weight	580 g

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0825 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.