

### Main

Commercial Status	Commercialised
Product or component type	AS-Interface Safety at work monitor
AS-i profile	7.F
Product specific application	For enhanced monitoring of safety devices
Number of safety circuits	2 NO + 2 NO
Discrete output number	2

### Complementary

Output type	Solid state
[Us] rated supply voltage	24 V DC (+/- 15 %)
Current consumption	44 mA AS-Interface line
[Ie] rated operational current	0.2 A
Response time	< 40 ms
Pick up duration	< 10000 ms
Input type	Opto-electronic coupler, 10 mAAt 24 V for start function Opto-electronic coupler, 10 mAAt 24 V for protection control function
Discrete output type	PNP transistor output(s), 0.2 mA
Protection type	External fuse
Associated fuse rating	<= 4 A
Enclosure material	Polyamide PA66
Fixing mode	Clip-on, mounting on symmetrical DIN rail conforming to EN 50022
Local signalling	2 LEDs yellow, function: restart signal 2 LEDs red, function: safety outputs open (on steady) or output error (flashing) 2 LEDs red, function: AS-Interface line fault 2 LEDs green, function: safety outputs closed 2 LEDs green, function: AS-Interface line supply
Product weight	0.45 kg

### Environment

Standards	EN 50081-2 EN 50295 EN 574 EN 61000-6-2 EN 954-1 category 4 EN/IEC 60204-1 EN/IEC 60947-5-1 EN/IEC 61496-1 IEC 61508 ISO 13849-1 category 4 ISO 13851
Product certifications	CSA TÜV UL
IP degree of protection	IP20
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-30...70 °C

## Contractual warranty

---

Period	18 months
--------	-----------

---