



### Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	1P + N
[I <sub>th</sub> ] conventional free air thermal current	16 A
I <sup>2</sup> t on activation	100000 A <sup>2</sup> .s
Number of points	1
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable length	0.2 m
Quantity per set	Set of 6

### Complementary

[U <sub>i</sub> ] rated insulation voltage	600 V conforming to UL 690 V conforming to IEC 60439-1 600 V conforming to CSA
Peak current	25 kA
Width	17.5 mm
Height	45.5 mm
Depth	38 mm
Product weight	0.035 kg

### Environment

Standards	IEC 60439
Product certifications	CSA DNV LROS (Lloyds register of shipping) UL

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.