



Main

Range of product	Modicon Momentum automation platform
Product or component type	Serial link option adaptor
Number of port	1
Communication port type	Single

Complementary

[Us] rated supply voltage	5 V DC
Input voltage tolerance	+/- 5 %
Supply	Via I/O base
Clock drift	+/- 13 s/day accuracy
Battery type	Lithium < 30 day after the battery low indication 40 °C
Battery size	2/3 AA
Battery life	5 yr
Communication port support	RS232 or RS485 serial link selectable
Electrical connection	1 connector D-shell 9 pins for Modbus Plus connection
Material	Lexan
Marking	CE
Local signalling	1 LED communication
Current consumption	700 mA 12 V DC
Height	25 mm
Width	143.1 mm
Depth	60.06 mm
Module format	Standard
Product weight	85.05 g

Environment

Dielectric strength	500 V DC
Standards	IEC 529
Product certifications	CSA NEMA 250 type 1 UL
IP degree of protection	IP20 IEC 529
Protective treatment	Conformal coating Humiseal 1A33 TC
Shock resistance	+/- 15 gn (duration = 11 ms) for half sine wave acceleration
Vibration resistance	1 gn 57...150 Hz
Amplitude of sinusoidal vibration	0.075 mm 10...57 Hz
Resistance to electrostatic discharge	8 kV on air IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...1000 MHz IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	5...95 % without condensation
Operating altitude	<= 2000 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status

Not Green Premium product

RoHS

Compliant - since 0826 - Schneider Electric declaration of conformity
