TM168GDB

Remote graphic display with buttons - 128 x 64 pixels for M168 base controller



Main

Range of product	Modicon M168 logic controller
Product or component type	Graphic display
Display type	LCD
Number of key	6
Display colour	Monochrome
Display resolution	128 x 64 pixels

Complementary

Memory type	Internal	
Backup time	10 years	
Number of read/write cycles	1000000	_
[Us] rated supply voltage	24 V AC/DC non isolated	_
Supply	External source	_
Supply voltage limits	1830 V	
Immunity to microbreaks	10 ms	_
Power consumption	<= 5 W	_
Local signalling	3 LEDs	_
Realtime clock	With clock, clock drift <= 30 s/month 2 days	_
Local signalling	1 LED green for power supply1 LED red for bus activity RX (reception)1 LED red for bus activity TX (transmission)	
Height	133 mm	
Width	112 mm	
Depth	36 mm	
Product weight	0.24 kg	

Environment

LIMIOIIIIEIIL		
Standards	EN 60730-1 EN 61000-6-1 EN 61000-6-3	
Product certifications	WEEE REACH CSA 60730-1 UL 60730-1	
Marking	CE	
Ambient air temperature for operation	055 °C	
Ambient air temperature for storage	-2070 °C	
IP degree of protection	IP40 on front face	
Pollution degree	2	
Overvoltage category	III	
Vibration resistance	3.5 mm (f = 5< 8.4 Hz conforming to EN/IEC 60028-2-6 1 gn (f = 8.4150 Hz conforming to EN/IEC 60028-2-6	
Shock resistance	15 gn for 11 ms	

Offer Sustainability

Sustainable offer status	Not Green Premium product	

