

Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2D
Product or component type	Switch-disconnector-fuse
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I _{th}] conventional free air thermal current	32 A at 40 °C
[I _e] rated operational current	20 A at 440 V 2 poles in series per phase on DC-23A 20 A at 440 V 2 poles in series per phase on DC-23B 32 A at 400 V on AC-23A 32 A at 400 V on AC-23B 32 A at 500 V on AC-23A 32 A at 500 V on AC-23B 32 A at 690 V on AC-23A 32 A at 690 V on AC-23B
Fuse type	BS
Fuse size	A1
Network type	AC DC
Network frequency	50/60 Hz

Complementary


Type of operating handle	External frontal External right side
Mounting support	Plate Rail
[U _i] rated insulation voltage	750 V AC 50/60 Hz
[U _{imp}] rated impulse withstand voltage	8 kV
Rated operational power in W	15 kW at 400 V 25 kW at 690 V 18.5 kW at 500 V
Making capacity	320 A at 400 V on AC-23B
[I _{cm}] rated short-circuit making capacity	80 kA at 400 V with protection by gG fuses
Breaking capacity	256 A at 400 V on AC-23B
Short-circuit withstand	9 kA
Mechanical durability	10000 cycles
Electrical durability	On DC-23A On DC-23B On AC-23A On AC-23B
Connections - terminals	Power circuit : screw-clamp terminals cable 6...25 mm ²
Tightening torque	Power circuit : 3.2 N.m

Environment


Standards	IEC 60947-3
Product certifications	CE
IP degree of protection	IP20 with terminal cover conforming to IEC 60529
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-40...80 °C
Fire resistance	960 °C body conforming to IEC 60695-2-1

Height	121 mm
Width	118 mm
Depth	87 mm
Product weight	0.8 kg

Door Cut-out - For External Front-mounted Operator



Door Cut-out - For External RH Side-mounted Operator



3-pole GS

