


GS2GB3

TeSys GS - switch-disconnector-fuse - 3 P - 63A -
BS A2, A3



Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2G
Product or component type	Switch-disconnector-fuse
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[Ith] conventional free air thermal current	63 A at 40 °C
[Ie] rated operational current	40 A at 440 V 2 poles in series per phase on DC-23A 40 A at 440 V 2 poles in series per phase on DC-23B 63 A at 400 V on AC-23A 63 A at 400 V on AC-23B 63 A at 500 V on AC-23A 63 A at 500 V on AC-23B 63 A at 690 V on AC-23A 63 A at 690 V on AC-23B
Fuse type	BS
Fuse size	A2 A3
Network type	AC DC
Network frequency	50/60 Hz

Complementary

Type of operating handle	External frontal External right side
Mounting support	Plate
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
Rated operational power in W	55 kW at 690 V 30 kW at 400 V 40 kW at 500 V
Making capacity	630 A at 400 V on AC-23B
[Icm] rated short-circuit making capacity	100 kA at 400 V with protection by gG fuses
Breaking capacity	500 A at 400 V on AC-23B
Short-circuit withstand	10.6 kA
Mechanical durability	10000 cycles
Electrical durability	On DC-23A On DC-23B On AC-23A On AC-23B
Connections - terminals	Power circuit : lugs-ring terminals cable 10...25 mm ²
Tightening torque	Power circuit : 3.2 N.m


Environment

Standards	IEC 60947-3
Product certifications	CE
IP degree of protection	IP20 with terminal cover conforming to IEC 60529
Ambient air temperature for operation	-20...70 °C


The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for storage	-40...80 °C
Fire resistance	960 °C body conforming to IEC 60695-2-1 850 °C fuse cover conforming to IEC 60695-2-1
Height	136 mm
Width	118 mm
Depth	116.5 mm
Product weight	1 kg

Door Cut-out - For External Front-mounted Operator



Door Cut-out - For External RH Side-mounted Operator



3-pole GS

