



Main

Commercial Status	Commercialised
Range of product	TeSys F
Product or component type	Contactor coil
Device short name	LX1FG
Control circuit type	AC 50/60 Hz
Control circuit voltage	265...277 V AC 60 Hz 220...230 V AC 50 Hz
Average resistance	16.5 Ohm at 20 °C
Inductance of closed circuit	2.59 H
Product compatibility	LC1F185 LC1F225
Operating time	7...15 ms opening 20...35 ms closing
Mechanical durability	10 Mcycles
Operating rate	2400 cyc/h at <= 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.85...1.1 U _c at 55 °C operational 50/60 Hz 0.35...0.55 U _c at 55 °C drop-out 50/60 Hz
Inrush power in VA	970 VA at 20 °C (cos φ 0.3) 60 Hz 805 VA at 20 °C (cos φ 0.3) 50 Hz
Hold-in power consumption in VA	66 VA at 20 °C (cos φ 0.3) 60 Hz 55 VA at 20 °C (cos φ 0.3) 50 Hz
Heat dissipation	18...24 W at 50/60 Hz

Environment

Ambient air temperature for operation	> -5...55 °C
Product weight	0.55 kg

Contractual warranty

Period	18 months
--------	-----------